

TTL flash GODOX iFlash iT32

Gamintojas: **GODOX** · Modelis: **iT32** · EAN: **6952344245729** · Prekės kodas: **641316**



91,90 €

Kaina su PVM

Be PVM: **75,95 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Godox iFlash iT32 TTL Flash

The Godox iFlash iT32 is a compact flash that gives photographers the freedom to work with various camera systems and offers a wide range of creative lighting options. Thanks to its modular design with a magnetic mount and compatibility with optional X5 series triggers, you can easily adapt it to your existing equipment. Support for TTL auto mode, HSS synchronization, and the Godox X 2.4 GHz wireless system allows you to work efficiently whether the flash is mounted on the camera or positioned off-camera. A color touchscreen, a high-capacity battery, and a fast flash recharge time make it easy to handle even intensive photo shoots. The package is rounded out by an LED modeling light and practical accessories, making the iFlash iT32 ideal for portrait photography, events, and outdoor shoots.

One flash, many possibilities

The Godox iFlash iT32's modular design allows you to use a single flash with cameras from various manufacturers. Simply connect it to the appropriate X5 series trigger—which attaches magnetically—to access TTL auto mode and sync with fast shutter speeds. Variants are available: the X5C for Canon cameras, the X5N for Nikon, the X5S for Sony, the X5F for FUJIFILM, and the X5O for Olympus/Panasonic. This solution makes it easy to adapt the lighting kit to different camera systems without having to replace the entire flash. This is particularly useful for photographers who work with multiple cameras or plan to change their equipment in the future. The X5C, X5N, X5S, X5F, and X5O triggers are sold separately and are not included in the kit.

Full control over every flash

The Godox iFlash iT32 offers three operating modes that allow you to tailor the lighting to the nature of the scene you’re photographing. The automatic TTL mode selects the flash exposure, making it easier to shoot in changing conditions, while Manual mode lets you set the power yourself within a wide range from 1/128 to 1/1. There is also a Multi mode, which allows you to fire a series of flashes during a single exposure to create striking motion shots. The FEC function allows you to further adjust the flash exposure to more precisely balance the lighting of the subject and its surroundings. Meanwhile, HSS synchronization with shutter speeds up to 1/8000 s provides greater freedom when shooting in bright ambient light, such as when taking portraits on a sunny day.

Wireless Freedom with the Godox X System

The integrated Godox X 2.4 GHz radio system expands the capabilities of the iFlash iT32, allowing it to be used in a variety of lighting setups. The unit supports wireless triggering both on-camera and off-camera, allowing you to experiment more freely with the direction of light and the flash’s position relative to the subject. Compatibility with the Godox ecosystem includes, among others, the X2T, XPro II, and X3 transmitters. This makes it easier to integrate the iFlash iT32 into your existing lighting setup and use it during more complex photo shoots.

Intuitive Operation and Additional LED Light

The color touchscreen provides convenient access to the flash’s settings and makes it easy to adjust them while shooting. The clear interface allows you to efficiently adjust the flash parameters to current conditions without having to interrupt your work for long. The Godox iFlash iT32 is also equipped with an LED modeling light featuring 10 brightness levels. This feature makes it easier to assess the scene’s lighting and prepare the right composition before taking the photo. The combination of touch controls and an additional light source makes the flash convenient to use during both fast-paced sessions and when carefully preparing each shot.

Power for Long Sessions and Easy Transport

The built-in 7.2 V, 900 mAh rechargeable battery allows for up to 510 full-power flashes on a single charge, ensuring sufficient power for extended use. A flash recycle time of just 1.5 seconds makes it easy to photograph dynamic events and take consecutive shots without long waits. Despite its wide range of features, the Godox iFlash iT32 remains compact (approximately 10.16 × 5.59 × 3.81 cm), so you can easily carry it in your camera bag.

Included

- Godox iFlash iT32 TTL flash
- USB charging cable
- Magnetic mini tripod
- Diffuser
- Magnetic color filter (orange)
- Storage bag
- Cleaning cloth
- User manual

Manufacturer	GODOX
Model	iFlash iT32
Flash duration (t0.1)	1/1000 s – 1/30,000 s
Exposure control system	TTL auto flash and manual flash
Flash exposure compensation	±3 stops in 1/3-stop increments
Synchronization mode	High-speed sync (up to 1/8,000 second or 1/80,000 second for Sony cameras with a global shutter), first-curtain sync, and second-curtain sync

Multi-flash mode	Built-in (up to 100 times, 100 Hz)
Wireless Function	Transmitter, receiver
Transmitter Groups	M, A, B, C (iT32+X5S/N/F/O) A, B, C, D (iT32+X5C) (X5 trigger sold separately)
Receiver groups	A, B, C, D
Transmission range	Max. 80 m (max. 20 m in standalone trigger mode)
Channels	32: 1-32
ID	OFF/1-99
Flash recycle time (1/1 step)	Approx. 1.5 s
Number of flashes (1/1 step)	Approx. 510

GPSR Link: https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photographic_studio.pdf, PPWR:

<https://ppwr.innpro.pl/en/godox>, Gross weight: 330, Box length: 13,00, Box width: 10,00, Box height: 7,00, Net weight: 258

Techninė specifikacija

Specifications

Sandėlio grupė Photo and cameras/Photo studio/Lamps [+75][-32]

Matmenys ir svoris

Matmenys (l × P × A) 13,00cm × 10,00cm × 7,00cm

Svoris 0,33kg