

Axagon BUCM4X-CM10AB USB kabelis USB4 Gen 3x2 1 m USB C 40 Gbit/s 240 W Juoda

Gamintojas: **AXAGON** · Modelis: **BUCM4X-CM10AB** · EAN: **8595247907967** · Prekės kodas: **641791**



18,90 €

Kaina su PVM

Be PVM: **15,62 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1 m
- ✓ USB C Tiesus Kištukinis
- ✓ USB C Tiesus Kištukinis
- ✓ USB4 Gen 3x2 Spartusis įkrovimas „USB Power Delivery“ 3.1 240 W
- ✓ Juoda
- ✓ 1 vnt



Aprašymas

Premium connection USB-C <-> USB-C Data and Charging AXAGON BUCM4X-CM10AB NewGen+ cable with USB-C male connectors at both ends. The cable has a full-featured USB 40Gbps specification (USB4 Gen 3x2) connection and is fully compatible with Thunderbolt 3 and Thunderbolt 4 specifications. It is designed for the fastest data transfer, video transfer and charging of laptops, phones, tablets. Allows connection of monitors, docking stations and external SSDs.

The cable supports up to 40 Gb/s data transfer and also allows image transfer up to 8K/60Hz Full Ultra HD resolution and audio.

The cable has implemented the latest specification of Power Delivery 3.1 charging technology. This technology delivers, among other things, a power output of 240W which is more than double that of Power delivery 3.0, which delivers 100W. You can use not only the Standard Power Range (SPR) for voltages of 5, 9, 15 and 20V with a current of 5A, but also sufficient power in fixed voltages of 28, 36 and 48V with a maximum current of 5A (Extended Power Range - EPR). Thanks to the new PD 3.1 technology, you can also use the cable to power devices with much more power, such as gaming laptops, 8K monitors, docking stations. To identify the cable and its current capabilities, the cable has an integrated E-Mark chip.

The cable is also compatible with Quick Charge, PPS, Samsung AFC and SFC, Apple, SMART and other charging technologies.

Cable conductors are made of Tin-plated oxygen free copper. Power cables 22AWG (lower number = larger cross-section and lower wire resistance) and 32AWG data wires guarantee fast charging and reliable data transfer of connected devices. High-quality cable insulation, made of flexible TPE, guarantees maximum durability and also maintains sufficient flexibility. Triple shielding protects transmitted signals from adverse interference.

The cable is equipped with aluminum end caps, connectors with nickel-plated surface and gold-plated contacts. The final strength of the cable is provided by the nylon braid. The braid in combination with a cable gland significantly reduces dangerous cable bending. The cable life is extended to more than 8000 standard bends.

The bonus is the included practical strip for easy packing of the cable.

Connectors:

- 2x USB-C (M) male.

Data and video transfer, charging:

- 40 Gb/s, 8K/60Hz HDR10
- Power Delivery 3.1 - 240W (48V/5A)

Other features:

- DATA SYNC & FAST CHARGING - simultaneous data and video transfer and mobile device charging.
- Support for third generation transfer rates of 40 Gb/s.
- USB4 Gen 3x2 Full-featured.
- Compatible with Thunderbolt 4, Thunderbolt 3 (including Apple support).
- Support for second generation transmission rates 20 / 10 Gb/s.
- Compatible with USB4 Gen 2x2, USB 3.2 Gen 2x2 / USB 3.2 Gen 2.
- Supports transfer rates of 5.000 / 480 Mb/s.
- Compatible with USB 3.2 Gen 1 (before USB 3.1 Gen 1 / USB 3.0) / USB 2.0.
- DisplayPort 1.4a, 2.0 protocol support for audio and video transmission up to Full Ultra HD 8K@60Hz, HDR10 resolution - a USB-C port with DisplayPort Alternate Mode (DP Alt Mode) support or a Thunderbolt 3/4 port is required.
- Supported charging technologies: Power Delivery 2.0 / 3.0 / 3.1 240W (48V/5A), Qualcomm Quick Charge 2.0 / 3.0 / 4+, Samsung Adaptive Fast Charging, Huawei Fast Charge Protocol, SMART Charging and others.
- Support for fast charging with a current of up to 5A.
- Integrated E-MARK chip.
- Cable includes power wires 22AWG, data wires 32AWG.
- Tin-plated oxygen free copper conductors to reduce oxidation, increase conductivity, and clear signal without distortion.

- Double shielding via galvanized foil and tinned copper braiding minimizes interference and prevents signal loss.
- Nickel-plated connectors and gold-plated contacts prevent oxidation and provide a reliable connection.
- Suitable for MacBooks, iPhone 15 Pro / Pro Max, notebooks, mobile phones and smartphones, tablets, power banks, chargers, monitors, docking stations, external SSD drives and other mobile devices with a USB-C connector.

Other data:

- cable length 1 m,
- outer diameter of the cable 5 mm.

Package contains:

- USB-C M <-> USB-C M black cable,
- tightening strip,
- packed in sealed foil package with hanging hole.

Techninė specifikacija

Savybės	
USB versija	USB4 Gen 3x2
Jungtis 1	USB C
Jungtis 2	USB C
1 jungtis – vidinė ar išorinė	Kištukinis
2 jungtis – vidinė ar išorinė	Kištukinis
Produkto spalva	Juoda
1 jungties forma	Tiesus
2 jungties forma	Tiesus
AWG laido dydis	22/32
Jungties medžiaga	Nikelis
Jungties kontaktų dengimas	Auksas
Laido dangos medžiaga	Termoplastinis elastomeras (TPE)
Kabelio apvalkalo tipas	Pintas
Konduktoriaus medžiaga	Neoksiduotas varis
Jungties ekranavimas	Taip
Jungties ekranavimo medžiaga	Aliuminis
Jungties korpuso medžiaga	Aliuminio
Maksimalaus duomenų perdavimo sparta	40 Gbit/s
Kabelio tipas	Apvalusis kabelis
Spartusis įkrovimas	Taip
„USB Power Delivery“	Taip
USB maitinimo šaltinio peržiūra	3.1
USB maitinimo tiekimas iki	240 W

„USB Type C DisplayPort Alternate Mode“	Taip
Maksimali rezoliucija	7680 x 4320 pikseliai
Maksimalus atnaujinimo dažnis	60 Hz
Palaikoma HDR	Taip
Didelio dinaminio diapazono (HDR) technologija	High Dynamic Range 10 (HDR10)
Suderinami produktai	MacBooks, iPhones, notebooks, mobile phones and smartphones, tablets, power banks, chargers, monitors, docking stations, external SSD drives and other mobile devices with a USB-C connector.
Energijos valdymas	
Iėjimo įtampa	48 V
Įvesties srovė (maks.)	5 A
Svoris ir matmenys	
Kabelio ilgis	1 m
Kabelio skersmuo	5 mm
Svoris	55 g
Pakuotės duomenys	
Pakuotės tipas	Krepšys
Pakuotės plotis	130 mm
Pakuotės gylis	10 mm
Pakuotės aukštis	205 mm
Paketo svoris	60 g
Pakuotės turinys	
Kiekis pakuotėje	1 vnt
Sertifikatai	
Atitikties sertifikatai	RoHS, CE
Sertifikavimas	CE, RoHS
Logistikos duomenys	
Kilmės šalis	Kinija
Garantinis laikotarpis	3 metai
Matmenys ir svoris	
Matmenys (I × P × A)	1,00cm × 13,00cm × 21,00cm
Svoris	0,06kg

Gamintojo ir saugos informacija

GAMINTOJAS

RealQ, s.r.o.

Železná 663/5, 619 00 Brno-jih, CZ

axagon.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt