

Dahua Technology WizSense IPC-HDW2449TM-S-IL-0280B security camera Dome IP security camera Outdoor 2688 x 1520 pixels Ceiling

Gamintojas: **DAHUA TECHNOLOGY** · Modelis: **IPC-HDW2449TM-S-IL-0280B** · EAN: **6923172580368** · Prekės kodas: **642196**



122,90 €

Kaina su PVM

Be PVM: **101,57 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image
- ✓ Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps
- ✓ H.265 codec, high compression rate, ultra-low bit rate
- ✓ Built-in warm light/IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m
- ✓ ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- ✓ Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- ✓ Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)
- ✓ Supports max. 256 G Micro SD card; built in MIC
- ✓ 12 VDC/PoE power supply, easy for installation
- ✓ IP67 protection



Techninė specifikacija

Specifications

Sandėlio grupė

Root/Electronics/Networks and communication/Monitoring/Monitoring IP [+33][-323]

Performance

Type	IP security camera
Placement supported	Outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Dynamic range	120 dB

Design

Mounting type	Ceiling
Product colour	White
Form factor	Dome
Housing material	Metal, Plastic
International Protection (IP) code	IP67

Camera

Camera pan control	Yes
Camera tilt control	Yes
Minimum illumination	0.0006 lx
Angle of rotation	360°
Lens viewing angle, horizontal	95°
Lens viewing angle, vertical	52°
Lens viewing angle, diagonal	114°
Tilt angle range	0 - 78°
Pan range	0 - 360°
White balance	Auto, Manual, Natural, Outdoor, Regional custom, Street lamp
Camera shutter speed	1/3 - 1/100000 s
Number of Privacy masking areas	4

Image sensor

Sensor type	CMOS
Number of sensors	1
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")
Progressive scan	Yes

Lens system

Detect distance	63.6 m
-----------------	--------

Observe distance	25.4 m
Recognize distance	12.7 m
Fixed focus	Yes
Maximum aperture number	1.6
Identify distance	6.4 m
Fixed focal length	2.8 mm
Closest focusing distance	0.9 m
Night vision	
Night vision	Yes
Night vision distance	30 m
Colour night vision distance	30 m
LED type	IR
Number of illumination LEDs	2
Video	
Maximum resolution	2688 x 1520 pixels
Total megapixels	4 MP
Video compression formats	H.264, H.264B, H.264H, H.265, M-JPEG
Video recording	Yes
Frame rate	30 fps
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Gain control type	Auto/Manual
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Region of Interest (ROI) encoding	Yes
Audio	
Audio formats supported	G.711, G.711 μ -law, G.726, PCM
Built-in microphone	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No

Ethernet interface type	Fast Ethernet
Networking standards	IEEE 802.1x, IEEE 802.3af
Supported network protocols	IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, NTP, ICMP, IGMP, P2P
Streaming method	Multicast
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB
ROM capacity	128 MB
RAM capacity	128 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
DC-in jack	Yes
Security	
Video motion detection	Yes
IP address filtering	Yes
Mirror	Yes
Human and vehicle targets classification	Yes
Power	
Power source type	DC, PoE
Power consumption (typical)	2.1 W
Power consumption (max)	4.4 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-40 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
System requirements	
Mobile operating systems supported	Android, iOS
Weight & dimensions	
Height	99.1 mm
Diameter	12.2 cm
Weight	460 g

Packaging data	
Package weight	650 g
Sustainability	
Compliance certificates	CE, Federal Communications Commission (FCC), UL
Packaging content	
Number of cameras	1
Manual	Yes
Matmenys ir svoris	
Matmenys (l × p × A)	14,00cm × 12,00cm × 14,00cm