

i-tec USB-C Dual Display Docking Station with Power Delivery 100 W + Universal Charger 100 W

Gamintojas: **I-TEC** · Modelis: **C31DUALDPDOCKPD100W** · EAN: **8595611703799** · Prekės kodas: **642796**



111,90 €

Kaina su PVM

Be PVM: **92,48 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Compatible with USB-C and Thunderbolt laptops & tablets. (The host device must support DisplayPort Alt mode)
- ✓ 2x DisplayPort supporting up to dual 4K/60Hz or a single 5K/60Hz display (depending on host performance). macOS supports a single extended display only
- ✓ 6x USB-ports (5x USB-A, 1x USB-C) make it easy to connect multiple USB devices and peripherals
- ✓ Provides up to 100W Power Delivery for compatible USB-C and Thunderbolt laptops & tablets. The host device must support USB-C Power Delivery
- ✓ GLAN Ethernet supports network speeds of 10/100/1000 Mbps speeds, providing a robust and high-speed internet connection
- ✓ Combo 3.5 mm audio input/output jack for easy connection to headset or speakers
- ✓ VESA bracket available to help keep your desk tidy and free from cables, plus K-lock slot for added security
- ✓ Power-saving On/Off switch to reduce energy consumption when the docking station is not in use
- ✓ Note: 100W power supply included. The dock can also be used with the USB-C PSU supplied with your laptop, so is available as a standalone item, P/N C31DUALDPDOCKPD



Aprašymas

USB-C office docking station with support for up to 2 external monitors with 4K resolution. The station is compatible with any laptop equipped with a USB-C or Thunderbolt 3 port. 6x USB ports, reliable and quick connection to your business network thanks to an integrated LAN port and support for installation behind a monitor make the docking station an ideal partner for professionals. And of course, the station is capable of charging your laptop or tablet with up to 100 W.

Integrated latest DP 1.4 protocol supports 5K/60 Hz resolution, making the device suitable for even professional graphics designers, data analysts, film editors and, of course, fans of HD video.

The docking station also comes with a USB-C power adapter with a total power of 100 W (USB-C port: 100 W)

Should you need to connect your monitor via an HDMI port, you can purchase DP2HDMI4K60HZ (i-tec DisplayPort to HDMI Adapter), to allow HDMI connection with resolution of up to 4K and refresh rate of up to 60 Hz.

Note: macOS does not support Multi Stream Transport (MST) technology. Connecting two monitors to the station on macOS will result in both monitors showing the same image.

- Connect up to two 4K/30 Hz external monitors
- Power delivery: up to 100 W (USB-C power adapter with a total power of 100 W is included)
- Two available DisplayPorts
- 3x USB 3.1, 1x USB-C 3.1 and 2x USB 2.0 for easy connection of your USB devices and peripherals. Gigabit Ethernet RJ-45 provides reliable, robust and high-speed Internet connection supporting 10/100/1000 Mbps speeds
- Combined jack for audio and microphone on the front panel
- Kensington lock protects against theft, particularly in shared offices or public spaces
- On/off switch for maximum energy savings
- The station features VESA support, allowing smart vertical installation behind a VESA compatible monitor
- Supports Windows 10, macOS X, Android, ChromeOS and Linux

Techninė specifikacija

Specifications	
Sandėlio grupė	Root/Accessories Exploitation/Cables and adapters/Docking stations and port replicators [+29][-59]
Ports & interfaces	
Connectivity technology	Wired
Host interface	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 2.0 ports quantity	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
HDMI ports quantity	0
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	2
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	100 W
DisplayPorts quantity	2
Combo headphone/mic port	Yes
Headphone connectivity	3.5 mm

Network

Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000 Mbit/s

Performance

Product colour	Black
Card reader integrated	No
Cable lock slot	Yes
Cable lock slot type	Kensington
VESA mounting	Yes
On/off switch	Yes
LED indicators	Yes

Power

Power source type	AC
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Input current	2.3 A
Power supply	100 W
Output voltage	5 / 9 / 12 / 15 / 19 / 20 V
Output current	5 A
Compatible power plug types	EU

Software

Windows operating systems supported	Yes
Mac operating systems supported	Yes
Linux operating systems supported	Yes
Other operating systems supported	Android

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 100%

Weight & dimensions

Width	113 mm
Depth	113 mm
Height	40 mm

Packaging data

Package width	338 mm
---------------	--------

Package depth	150 mm
---------------	--------

Package height	55 mm
----------------	-------

Package weight	998 g
----------------	-------

Packaging content

Cables included	AC
-----------------	----

AC adapter included	Yes
---------------------	-----

Manual	Yes
--------	-----

Logistics data

Harmonized System (HS) code	84733020
-----------------------------	----------

Matmenys ir svoris

Matmenys (I × P × A)	34,00cm × 16,00cm × 6,00cm
----------------------	----------------------------