

i-tec Universal Charger USB-C PD 3.1 140 W

Gamintojas: **I-TEC** · Modelis: **CHARGER-C140W** · EAN: **8595611707209** · Prekės kodas: **642846**



40,90 €

Kaina su PVM

Be PVM: **33,80 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Universal USB-C charger with a maximum power of 140 W
- ✓ Suitable for powering notebooks, tablets, smartphones, and other devices equipped with a USB-C charging port (140 W is available if it supports a USB-C PD 3.1 protocol, otherwise 100W will be provided)
- ✓ The voltage is automatically adjusted according to the requirement of your device
- ✓ Available voltages: 5 V / 9 V / 12 V / 15 V / 20 V / 28 V
- ✓ Max current: 5A
- ✓ Damage- and overheat-resistant design



Aprašymas

This universal USB-C power adapter with power of 140 W * is a great choice for powering any laptop or other device equipped with a USB-C connector that supports USB-C Power Delivery with a maximum power demand of 140 W *.

The voltage is set automatically according to the USB Power Delivery specification and individual profiles in following steps: 5 V / 9 V / 12 V / 15 V / 20 V / 28 V with max. 5 A current consumption.

The power adapter is lightweight and very portable; it is equipped with intelligent current overload, overvoltage, short circuit and overheating protection.

* If your notebook or tablet supports the new and modern USB-C Power Delivery PD 3.1 charging protocol, the charger will offer charging power up to 140W (if you have PD 3.0, the charging power will be 100W)

Techninė specifikacija

Specifications	
Sandėlio grupė	Root/Accessories Exploitation/Laptop accessories/Power supply units [+37][-169]
Performance	
Charger type	Indoor
Charger compatibility	Laptop, Smartphone, Tablet
Power source type	AC
Number of simultaneously connected devices (max)	1
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3.1
Power protection features	Overheating
Design	
Product colour	Black
Power	
Input voltage	100-240 V
Input frequency	50-60 Hz
Input current	1.8 A
Maximum power	140 W
Maximum output voltage	28 V
Minimum output voltage	5 V
AC adapter output current	5 A
Efficiency (@10 %)	83%
Packaging data	
Package width	127 mm
Package depth	30 mm
Package height	70.5 mm
Package weight	379 g
Operational conditions	
Operating temperature (T-T)	0 - 35 °C
Packaging content	
Manual	Yes

Included power plug types

EU