

TP-Link EAP110 wireless access point 300 Mbit/s White Power over Ethernet (PoE)

Gamintojas: **TP-LINK** · Modelis: **EAP110** · EAN: **1210002618434** · Prekės kodas: **642916**



35,90 €

Kaina su PVM

Be PVM: **29,67 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Cloud centralized management and Omada app for ultra convenience and easy management
- ✓ Supports passive PoE for convenient installation up to 100meters2
- ✓ Ceiling mounting design with chassis makes it easy to deploy on a wall or ceiling
- ✓ The captive portal provides modern and professional user sign-in experience
- ✓ Facebook check-in and SMS authentication expands your social exposure with secured technology
- ✓ Multi-SSID divides multiple wireless networks for different user groups
- ✓ Enterprise class Wi-Fi security help to decrease network security threats
- ✓ Supports management VLAN for an enhanced network management



Aprašymas

Flexible Placement

Easy mounting design & PoE

The EAP's elegant appearance and easy mounting design with chassis make it easy to be integrated seamlessly into any wall or ceiling surface to blend in with most interior decorations. EAP110 supports Passive PoE to make deployment effortless and flexible.

Cloud Centralized Management

- Anytime, Anywhere

Omada Hardware Controller OC200 and Omada Software Controller make it easy to manage and monitor the whole Omada network in real-time, while cloud service enables remote and secure access no matter where you find yourself.

Efficient Guest Authentication with Facebook and SMS Support

Captive portal helps maintain only authorized guests to use the network, presenting devices with a convenient, user-friendly authentication method to grant Wi-Fi access. The addition of SMS and Facebook authentication simplifies the captive portal even further to simplify connectivity and boost your business.

Easy Management with the Omada App

Follow configuration instructions on the free Omada app to get set up in minutes. Omada lets you configure settings, monitor the network status and manage clients, all from the convenience of a smart phone or tablet.

Meet Our New Hero Product!

The OC200 Omada Hardware Controller is dedicated to providing centralized management for the whole Omada network.

Techninė specifikacija

Specifications	
Sandėlio grupė	Root/Electronics/Networks and communication/Access points [+7][+119]
Features	
2.4 GHz	Yes
5 GHz	No
Maximum data transfer rate	300 Mbit/s
Maximum data transfer rate (2.4 GHz)	300 Mbit/s
Ethernet LAN data rates	10,100 Mbit/s
Frequency band	2.4 - 2.4835 GHz
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x
Cabling technology	10/100Base-T(X)
Automatic channel selection	Yes
Wi-Fi Multimedia (WMM)/(WME)	Yes
VLAN support	Yes
Virtual LAN features	SSID-based VLAN assignment
Rate limiting	Yes
Wireless isolation	Yes
Quality of Service (QoS) support	Yes
Transmitting power (CE)	21 dBm
Receiver sensitivity	300M: -71dBm@10% PER 150M: -75dBm@10% PER 54M: -78dBm@10% PER 11M: -93dBm@8% PER 6M: -92dBm@10% PER 1M: -96dBm@8% PER
Security	

Security algorithms	64-bit WEP, 128-bit WEP, 152-bit WEP, HTTPS, SNMP, SNMPv2, SSH, WPA, WPA-PSK, WPA2-Enterprise, WPA2-PSK
MAC address filtering	Yes
Service Set Identifier (SSID) features	Multiple SSIDs
Number of SSID supported	8
Remote Authentication Dial-In User Service (RADIUS)	Yes
Access Control List (ACL)	Yes
Management features	
Web-based management	Yes
Syslog	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
USB 2.0 ports quantity	0
Power	
Power over Ethernet (PoE)	Yes
AC input voltage	24 V
Power consumption (typical)	2.8 W
Design	
Placement	Ceiling, Wall
Product colour	White
Reset button	Yes
LED indicators	Power
Antenna	
Antenna type	Internal
Antenna direction type	Omni-directional
Antennas quantity	2
Antenna gain level (max)	4 dBi
Certificates	
Certification	FCC, RoHS
Weight & dimensions	
Width	189.4 mm
Depth	172.3 mm
Height	29.5 mm
Packaging data	

Package type	Box
Packaging content	
Quantity per pack	1 pc(s)
PoE adapter included	Yes
Cables included	AC
Mounting kit	Yes
Quick start guide	Yes
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%
Logistics data	
Harmonized System (HS) code	85176990
Matmenys ir svoris	
Matmenys (I × P × A)	7,00cm × 27,00cm × 24,00cm