

Cudy P2 wireless router 2.5 Gigabit Ethernet Dual-band (2.4 GHz / 5 GHz) 5G White

Gamintojas: CUDY · Modelis: P2 · EAN: 6971690793777 · Prekės kodas: 642958



142,90 €

Kaina su PVM

Be PVM: 118,10 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 5G Rel. 15 with Max 2.6 Gbps DL
- ✓ 5G/4G Dual Connectivity, 4x4 MIMO
- ✓ 4-Stream Dual-Band Wi-Fi 6
- ✓ 2402 Mbps + 574 Mbps Wi-Fi
- ✓ 2x Gigabit Ethernet Ports
- ✓ 1x Nano SIM Slot
- ✓ Cudy Mesh, VPN Server and Client
- ✓ Cudy App, Cloud Control



Aprašymas

Lightning-Fast 5G. Max 2.6 Gbps Download.

Unlock the lightning 5G connectivity that rivals a broadband connection. P2 provides download speed up to 2.6 Gbps with universal compatibility with major carriers plan.

150% Faster Wi-Fi Speed

The high-capacity AX3000 Wi-Fi 6 built with powerful 1.3 GHz dual-core CPU provides super-fast connection for every devices. Stream 4K live feed and download at full speed with ease.

Home

Plug and play easy-to-install WiFi for every home—no rigid broadband subscription.

Automobile

Provide decent networks for all devices on your road journey.

Surveillance

Make sure the network is always on with the backup function.

Booth

Utilize the flexible pay-as-you-go SIM card plan to equip your temporary booth with a fast network. (SIM card is not included)

Connect and Boost with Ease

Two Gigabit Ethernet ports provide stable wired network sharing. Two SMA connectors allow you to install customized extension cellular antennas.

Secure VPN Access

In addition to the management via Cudy cloud, this router supports multiple VPN protocols to enable remote Work-From-X, or sharing a commercial VPN for all.

Keep You Connected

Set the WAN/LAN port as WAN mode, connect your network to broadband service, then back it up with a WISP and a 5G connection.

A 5G WiFi 6 router with a max 2.6 Gbps download speed. It features one SIM slot, a high-capacity AX3000 WiFi 6 for high-speed internet. The ISP clients can add a RJ11 port for VoIP/VoNR service.

Techninė specifikacija

Specifications	
Sandėlio grupė	Root/Electronics/Networks and communication/Routers [+44][-296]
WAN connection	
Ethernet WAN	Yes
SIM card slot	Yes
3G/4G USB modem compatibility	Yes
Wireless LAN features	
Wi-Fi band	Dual-band (2.4 GHz / 5 GHz)
Top Wi-Fi standard	Wi-Fi 6 (802.11ax)
WLAN data transfer rate (max)	2402 Mbit/s
Wi-Fi standards	Wi-Fi 6 (802.11ax), 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
WLAN data transfer rate (first band)	574 Mbit/s
WLAN data transfer rate (second band)	2402 Mbit/s
Modulation	4096-QAM

Network

Ethernet LAN	Yes
Ethernet LAN interface type	2.5 Gigabit Ethernet
Port forwarding	Yes
Port triggering	Yes
Dynamic DNS (DDNS)	Yes
Number of guest networks (2.4 GHz)	1
Number of guest networks (5 GHz)	1
VPN server	WireGuard OpenVPN IPsec ZeroTier PPTP L2TP

Mobile network

Mobile network generation	5G
2G standards	GPRS
3G standards	WCDMA
4G standard	LTE-FDD
5G standard	Sub6
5G bands supported	850,1600,1800,1900,2300,2500,2800 MHz
4G bands supported	800,850,900,1500,1900,2000,2300,2400,2600 MHz
3G bands supported	800,850,900,1800 MHz

Ports & interfaces

Ethernet LAN (RJ-45) ports	1
RJ-11 ports quantity	1
DC-in jack	Yes

Management features

Web-based management	Yes
Quality of Service (QoS) support	Yes
Reset button	Yes
WPS push button	Yes
MU-MIMO technology	Yes
MIMO	Yes

Security

Security algorithms	WPA, WPA2, WPA3
Firewall	Yes
Guest access	Yes
Filtering	Yes

MAC address filtering	Yes
IP address filtering	Yes
URL filtering	Yes
IGMP snooping	Yes
DMZ support	Yes
Protocols	
DHCP client	Yes
DHCP server	Yes
Universal Plug and Play (UPnP)	Yes
Design	
Product type	Tabletop router
Product colour	White
Antenna	
Antenna design	Internal
Antenna type	2x2
Antenna connector type	SMA
Detachable antenna(s)	Yes
Features	
Built-in processor	Yes
Processor architecture	ARM Cortex-A53
Processor frequency	1300 MHz
Processor cores	2
Internal memory	128 MB
Flash memory	256 MB
Power	
Power source type	DC
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Output voltage	12 V
Output current	1.5 A
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%

Storage relative humidity (H-H)	5 - 95%
---------------------------------	---------

Weight & dimensions

Width	116 mm
-------	--------

Depth	116 mm
-------	--------

Height	202 mm
--------	--------

Weight	650.8 g
--------	---------

Packaging data

Package width	313 mm
---------------	--------

Package depth	152 mm
---------------	--------

Package height	132 mm
----------------	--------

Package weight	1.08 kg
----------------	---------

Matmenys ir svoris

Matmenys (I × P × A)	14,00cm × 31,00cm × 15,00cm
----------------------	-----------------------------