

CyberPower CP900EPFCLCD uninterruptible power supply (UPS) Standby (Offline) 0.9 kVA 540 W 6 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **CP900EPFCLCD** · EAN: **4712364142468** · Prekės kodas: **643300**



228,90 €

Kaina su PVM

Be PVM: **189,17 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-interactive UPS Topology
- ✓ Active PFC Compatible
- ✓ Automatic Voltage Regulation (AVR)
- ✓ LED Status Indicator
- ✓ Surge and Spike Protection
- ✓ Tower Form Factor
- ✓ Energy Saving Technology
- ✓ Pure Sine Wave Output
- ✓ LCD Status Display
- ✓ PowerPanel Management Software



Aprašymas

The CyberPower Adaptive Sinewave™ Series offers users from home to SMEs clean and stable battery backup while the featured RJ11/RJ45 port ensures phone, fax, and modem lines are protected from surges. With Automatic Voltage Regulation (AVR) stabilizes the AC signal and maintains a safe voltage, this allows the UPS to maintain safe power levels for the connected equipment without resorting to battery power. The multifunction LCD readout provides immediate access to precise information of critical power/battery condition. The included PowerPanel® Personal Edition management software showcases the featured rich abilities such as input/output power voltage readings, self-diagnostics, scheduled-shutdown, and approximate battery backup time. With the Energy-Saving Technology, the Adaptive Sinewave™ Series can save up to 75% of electricity therefore save your electricity expenses.

Techninė specifikacija

Specifications	
Sandėlio grupė	Root/Accessories Exploitation/Power supply/UPSs and power strips/UPSs [+50][-350]
Features	
UPS topology	Standby (Offline)
Output power capacity	0.9 kVA
Output power	540 W
Waveform	Pure sine
Input operation voltage (min)	170 V
Input operation voltage (max)	270 V
Input frequency	50/60 Hz
Output frequency	50/60 Hz
Maximum current	10 A
Surge energy rating	405 J
Response time	4 ms
Output voltage Total Harmonic Distortion (THD)	10%
EMI/RFI noise filtering	Yes
Surge protection	Yes
Surge protection features	Fax, Modem, Network, Telephone
Power protection features	Over power, Over voltage, Overload, Short circuit
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm
Auto-restart	Yes
Ports & interfaces	
AC outlet types	Type F
Power plug	C14 coupler
AC outlets quantity	6 AC outlet(s)
USB 2.0 ports quantity	1
Modem (RJ-11) ports	1
Ethernet LAN (RJ-45) ports	1
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery voltage	230 V
Number of batteries supported	1

Typical backup time at full load	1 min
Typical backup time at half load	7 min
Battery recharge time	8 h

Design

Form factor	Tower
Product colour	Black
Housing material	Plastic
Cable length	1.83 m
Display type	LCD
LED indicators	Operation

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates

Certification	CE, EAC, RCM
---------------	--------------

Weight & dimensions

Width	100 mm
Depth	230 mm
Height	275 mm
Weight	6.6 kg

Packaging data

Package width	195 mm
Package depth	365 mm
Package height	335 mm
Package weight	7.8 kg

Logistics data

Harmonized System (HS) code	8504408590
Country of origin	China

Other features

Interface	USB
-----------	-----

Nominal output voltage	230 V
Nominal input voltage	165-265 V
Compatible operating systems	Windows 7/Vista/XP/2000/Server 2003, Linux
Operating temperature (T-T)	32 - 104 °F
Suitable for use in country/location	Europe
Matmenys ir svoris	
Matmenys (l × P × A)	37,00cm × 34,00cm × 20,00cm