

StarTech.com S5G16AINDS-USB-A-HUB sąsajos šakotuvas 2 x USB 3.2 Gen 1 (3.1 Gen 1) Type-B 5000 Mbit/ai Juoda

Gamintojas: **STARTECH** · Modelis: **S5G16AINDS-USB-A-HUB** · EAN: **065030905381** · Prekės kodas: **644582**



631,90 €

Kaina su PVM

Be PVM: **522,23 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Priimančioji sąsaja: 2 x USB 3.2 Gen 1 (3.1 Gen 1) Type-B
- ✓ Lizdo sąsajos: USB 3.2 Gen 1 (3.1 Gen 1) Type-A
- ✓ Portų kiekis: 16
- ✓ 5000 Mbit/ai
- ✓ Juoda Plienas



Aprašymas

Add 16x USB 3.2 Gen 1 (5 Gbps) ports to two host computers, using this DIN-rail/Surface/Rack-mountable industrial hub

The 16-Port Industrial USB 5Gbps Hub with Power Adapter features 16 downstream USB-A ports. The rugged all-metal construction is suitable for use in industrial rackmount applications. Level-4 Electrostatic Discharge (ESD) protection safeguards against 15kV Air / 8kV Contact discharges. The hub features a 2-port host switch, enabling users to switch between two host devices.

Engineered for Use in Industrial Environments

This USB hub is built to withstand harsh industrial environments. It features a rugged steel housing that protects against physical hazards such as drops and impacts. It is equipped with Level-4 ESD protection, with 15kV air and 8kV contact discharge ratings, to safeguard against damage caused by static electricity.

Three Mounting Options

The 16-Port USB hub can be attached to a surface (e.g., atop/underneath a desk or wall mounted), rack mounted, or DIN-rail mounted. The 19" rackmount rails are compliant with EIA-310-D standards, ensuring compatibility with standard racks. These rails can be used to install the USB hub into 1U of rack space for applications in data centers and server rooms. Mount industrial automation and control equipment in an electrical enclosure or cabinet, using the standard DIN-rail (Top Hat/TH) mounting hardware.

Power Adapter Included

This USB hub includes a 160W power adapter that connects to the 2-wire terminal block connector. When connected to the power adapter, the USB hub supports USB Battery Charging Specification 1.2 (BC 1.2) with 120W shared across all ports. Ports are grouped in 8 pairs (1&2, 3&4, 5&6, 7&8, 9&10, 11&12, 13&14, 15&16) and each pair supports a maximum of 3.0A/15W combined (1.5A/7.5W per port), or max 2.0A/10W per port when only one of both ports is used.

For optional power redundancy, the USB hub features a secondary power input where a barrel-power adapter (not included) can be connected. The barrel-power input supports a 12-to-24-volt input range, and can be ideal for mission critical applications.

Dual-Host Switch

The USB Hub connects to two desktop or laptop computers, and features a dual-host switch enables easy toggling between the host devices.

Enhance Productivity and Device Management with the StarTech.com Connectivity Tools Application

Developed to improve performance and security, StarTech.com Connectivity Tools is the only software suite on the market that is compatible with a wide variety of IT connectivity accessories. This product utilizes the USB Event Monitoring utility. Use this utility to track and log connected USB devices.

For more information and to download the StarTech.com Connectivity Tools application, please visit: www.StarTech.com/Connectivity-Tools

Techninė specifikacija

Ryšys	
Portų kiekis	16
Priimančioji sąsaja	2 x USB 3.2 Gen 1 (3.1 Gen 1) Type-B
Lizdo sąsajos	USB 3.2 Gen 1 (3.1 Gen 1) Type-A
USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius	16
Integruotas kortelių skaitytuvas	Ne

Gnybtų kaladėlės prievadas	Taip
----------------------------	------

DC įėjimo lizdas	Taip
------------------	------

Savybės

Duomenų perdavimo sparta	5000 Mbit/ai
--------------------------	--------------

Produkto spalva	Juoda
-----------------	-------

Korpuso medžiaga	Plienas
------------------	---------

Apsauga nuo elektrostatinės iškrovos (ESD; oras)	15 kV
--	-------

Apsauga nuo elektrostatinės iškrovos (ESD; kontaktas)	8 kV
---	------

LED indikatoriai	Energija, Būsena
------------------	------------------

„Plug and Play“ funkcija	Taip
--------------------------	------

Energijos valdymas

Galios suvartojimas (maks.)	158,4 W
-----------------------------	---------

Įėjimo įtampa	100 - 240 V
---------------	-------------

Įvesties srovė	3.5 A
----------------	-------

Išėjimo įtampa	24 V
----------------	------

Išėjimo srovė	6,6 A
---------------	-------

Svoris ir matmenys

Svoris	1,1 kg
--------	--------

Pakuotės duomenys

Pakuotės plotis	273 mm
-----------------	--------

Pakuotės gylis	368 mm
----------------	--------

Pakuotės aukštis	98 mm
------------------	-------

Paketo svoris	1,8 kg
---------------	--------

Pakuotės turinys

Kintamosios srovės adapteris	Taip
------------------------------	------

Pridėti kabeliai	Iš A tipo USB į B tipo USB
------------------	----------------------------

Pridėta gnybtų kaladėlė	Taip
-------------------------	------

Pridedamas DIN bėgelio rinkinys	Taip
---------------------------------	------

Greitos pradžios vadovas	Taip
--------------------------	------

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	0 - 60 °C
------------------------------------	-----------

Sandėliavimo temperatūros norma (T-T)	-20 - 75 °C
---------------------------------------	-------------

Darbo santykinės drėgmės diapazonas	5 - 95%
-------------------------------------	---------

Veikimo charakteristikos

Vidutinis laikas tarp trikčių (MTBF)	122383,8 h
Logistikos duomenys	
Pagrindinės (išorinės) dėžės plotis	508 mm
Pagrindinės (išorinės) dėžės ilgis	403 mm
Pagrindinės (išorinės) dėžės aukštis	318 mm
Gaminių skaičius pagrindinėje (išorinėje) dėžėje	5 vnt
Techninė informacija	
Atitikties sertifikatai	Prekybos susitarimų įstatymas (PSĮ)
Kitos savybės	
Stovo montavimas	Taip
Lustų rinkinys	Genesys Logic - GL3523
Tvarumas	
Tvarumo reikalavimų laikymasis	Taip
Matmenys ir svoris	
Matmenys (I × P × A)	37,00cm × 28,00cm × 10,00cm
Svoris	3,03kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [Vaizdo įrašas](#) youtube.com/watch?v=rufzNk3ERrU

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA
[startech.com](#)

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
[startech.com](#)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
[info@shopro.lt](#)