

StarTech.com USB32000SPT tinklo plokštė Eternetas 5000 Mbit/ai

 Gamintojas: **STARTECH** · Modelis: **USB32000SPT** · EAN: **065030851428** · Prekės kodas: **645267**


79,90 €

Kaina su PVM

 Be PVM: **66,03 €**

Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vielinis
- ✓ USB 3.2 Gen 1 (3.1 Gen 1) Eternetas
- ✓ Gigabitinis eternetas 5000 Mbit/ai 10/100/1000BaseT(X)
- ✓ Taikoma: Kompiuteris / knyginis kompiuteris Lustų rinkinys: ASIX - AX88179, VIA/VLI - VL811



Aprašymas

Add two Gigabit Ethernet ports and a USB 3.0 pass-through port to your laptop through a single USB 3.0 port

The USB32000SPT USB 3.0 to Dual Port Gigabit Ethernet Adapter lets you add two Gigabit Ethernet ports to your laptop or Ultrabook™ computer through a single USB 3.0 port, and features an integrated USB 3.0 pass-through port that keeps your USB port available for use with external storage or other peripherals. Each RJ45 port supports 10/100/1000 Mbps Ethernet and is fully compatible with IEEE 802.3i/u/ab standards.

This 2-port USB LAN adapter is a versatile solution for connecting to two separate physical networks simultaneously, leveraging the 5 Gbps speed of USB 3.0 to provide dedicated gigabit bandwidth to each port. The dual USB NIC is also ideal for providing dedicated physical network interfaces to virtual machine configurations. Great for IT administrators that require dual-homed or multi-homed host systems.

The USB 3.0 NIC supports IPv4/IPv6 packet Checksum Offload Engine (COE) and TCP large send offload to reduce the load on your CPU, as well as Jumbo Frames, full-duplex operation with 802.3x flow control, and VLAN tagging for an efficient and full-featured USB network adapter.

Techninė specifikacija

Ports & interfaces	
Connectivity technology	Wired
Host interface	USB
Interface	Ethernet
Ethernet LAN (RJ-45) ports	2
USB ports quantity	1
USB version	3.2 Gen 1 (3.1 Gen 1)
Network	
Maximum data transfer rate	5000 Mbit/s
Networking standards	IEEE 802.1Q, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u
Ethernet LAN	Yes
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Cabling technology	10/100/1000BaseT(X)
Auto MDIX IEEE	Yes
Jumbo frames support	Yes
Jumbo frames	4000
VLAN tagging	Yes
Maximum operating distance	100 m
Design	
Internal	No
Component for	PC/Laptop
Product colour	Black

Chipset	ASIX - AX88179, VIA/VLI - VL811
LED indicators	Yes
Certification	RoHS, CE, FC
Power	
USB powered	Yes
System requirements	
Compatible operating systems	- Windows 8 (32/64bit), 7 (32/64), Vista(32/64), XP(32/64) - Windows Server 2008 R2, 2003(32/64) - Mac OS 10.6 - 10.8 - Linux Kernel 2.6.14 - 3.5.0
Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Linux operating systems supported	Yes
Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	5 - 95%
Weight & dimensions	
Width	60 mm
Depth	75 mm
Height	16 mm
Weight	59 g
Packaging data	
Drivers included	Yes
Package width	143 mm
Package depth	171 mm
Package height	30 mm

Package weight	154 g
Packaging content	
Manual	Yes
Technical details	
Compliance certificates	CE, RoHS
Logistics data	
Harmonized System (HS) code	85176990
Master (outer) case width	306 mm
Master (outer) case length	586 mm
Master (outer) case height	362 mm
Products per master (outer) case	80 pc(s)
Other features	
Housing material	Plastic
Cable length	0.203 m
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	18,00cm × 15,00cm × 4,00cm
Svoris	0,15kg

Dokumentai ir vaizdo įrašai

> [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS	ATSAKINGAS ASMUO ES	PLATINTOJAS
StarTech.com Ltd.	StarTech.com Limited	MB KOMPIUTERIŲ GURU
Artisans Crescent 45, N5V 5E9 Ontario, London, CA	Laarderhoogtweg 25, 1101 EB Amsterdam, NL	V. Nagevičiaus g. 3, LT-08237 Vilnius
startech.com	startech.com	info@shopro.lt