

TP-Link TL-WA850RE Tinklo kartotuvus Balta 10, 100 Mbit/ai

 Gamintojas: **TP-LINK** · Modelis: **TL-WA850RE** · EAN: **6935364070199** · Prekės kodas: **645562**


19,90 €

Kaina su PVM

 Be PVM: **16,45 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Tinklo kartotuvus 300 Mbit/ai
- ✓ 10/100Base-T(X)
- ✓ „Wi-Fi“ Viena juosta (2,4 GHz) 300 Mbit/ai 802.11b, 802.11g, Wi-Fi 4 (802.11n)
- ✓ Balta



Aprašymas

- Range Extender mode boosts wireless signal to previously unreachable or hard-to-wire areas flawlessly
- Miniature size and wall-mounted design make it easy to deploy and move flexibly
- Easily expand wireless coverage at a push of Range Extender button
- Ethernet port allows the Extender to function as a wireless adapter to connect wired devices
- Tether App allows easy access and management using any mobile device

- LED Control function includes a Night Mode for peaceful sleep

Boost Your Wireless Network

Tired of Wi-Fi "dead zone"? TP-Link's range extender connects to your router wirelessly, strengthening and expanding its signal into areas it can't on its own. The device also reduces signal interference to ensure reliable Wi-Fi coverage throughout your home or office.

Easy Setup and

Flexible Placement

Press the WPS button on your router and the Range Extender button on your 850RE within 2 minutes to easily connect to the network. Once connected with an existing router, you can simply unplug and plug the TL-WA850RE back in a location for the best signal quality and coverage in your house, without needing to configure the extender again.

Ethernet Bridge

The TL-WA850RE's single Ethernet port allows the Extender to function as a wireless adapter to connect wired devices like Blu-ray® players, gaming consoles, DVRs and Internet TVs. At the same time, the device can share the wireless network as well.

Smart Signal Indicator Light

5 signal lights show the strength of signal that TL-WA850RE receives from the existing router, which can help to find the right location to place the range extender.

It's recommended that you choose a location where at least 3 signal light blue in order to guarantee a good performance.

Tether App for

Easy Use

Use any mobile device to easily access and manage various features, including the LED Control function's Night Mode, which allows you to enjoy a more peaceful night's sleep.

Techninė specifikacija

Veikimo charakteristikos	
Tipas	Tinklo kartotuvas
Duomenų perdavimo sparta	300 Mbit/ai
Eterneto LAN duomenų perdavimo norma	10,100 Mbit/ai
WPS paspaudžiamasis mygtukas	Taip
Palaikomos „Windows“ operacinės sistemos	Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 2000, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 x64, Windows 98SE, Windows NT, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Mac suderinamumas	Taip

Palaikomos MAC operacinės sistemos	Taip
Palaikoma operacinė sistema „Linux“	Taip
Antena	
Antenų kiekis	2
Antenos tipas	Vidinis
Perdavimo galios diapazonas	0 - 20 dBmW
Tinklas	
Ethernet LAN sąsajos tipas	Greitas ethernetas
Kabelių technologija	10/100Base-T(X)
Tinklo standartai	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
„Wi-Fi“	Taip
„Wi-Fi“ standartas	Wi-Fi 4 (802.11n)
Wi-Fi standartai	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Belaidis LAN duomenų perdavimo greitis (maks.)	300 Mbit/ai
„Wi-Fi“ dažnių juosta	Viena juosta (2,4 GHz)
Apsaugos algoritmų palaikymas	64-bit WEP, 128-bit WEP, WPA-PSK, WPA2-PSK
Ryšys	
Ethernet LAN (RJ-45) portų kiekis	1
Konstrukcija	
Produkto spalva	Balta
LED indikatoriai	Taip
Atstatymo mygtukas	Taip
Sertifikavimas	CE, FCC
Energijos valdymas	
AC įėjimo įtampa	100 - 240 V
AC įėjimo dažnis	50 - 60 Hz
Energijos suvartojimas	3,3 W
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 70 °C
Darbo santykinės drėgmės diapazonas	10 - 90%
Sandėliavimo santykinis drėgmės diapazonas	5 - 90%
Svoris ir matmenys	
Plotis	110 mm

Ilgis	66 mm
Aukštis	75 mm
Pakuotės turinys	
Greitos pradžios vadovas	Taip
Pakuotės duomenys	
Pakuotės plotis	156,5 mm
Pakuotės gylis	101,5 mm
Pakuotės aukštis	89 mm
Paketo svoris	200 g
Sertifikatai	
Atitikties sertifikatai	RoHS
Logistikos duomenys	
Darniosios sistemos (DS) kodas	85176990
Matmenys ir svoris	
Matmenys (l × P × A)	11,00cm × 16,00cm × 9,00cm

Dokumentai ir vaizdo įrašai

- › Gaminio lankstinukas
- › Vaizdo įrašas 1 [objects.icecat.biz/objects/15759189_24187458.mp4](objects.icecat.biz/objects/15759189_24187458.mp4)
- › Vaizdo įrašas 2 [objects.icecat.biz/objects/15759189_5121287.mp4](objects.icecat.biz/objects/15759189_5121287.mp4)

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH

Niederkasseler Lohweg 175, 40547 Düsseldorf,
DEtp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt