Zyxel GS1200-8V3 Managed L2 Gigabit Ethernet (10/100/1000) Desktop Grey

Gamintojas: **ZYXEL** · Modelis: **GS1200-8V3** · EAN: **4718937649945** · Prekės kodas: **645763**

27,90 €

Kaina su PVM

Be PVM: **23,06 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Managed L2 Web-based management
- ✓ Quality of Service (QoS) support
- ✓ Basic switching RJ-45 Ethernet ports quantity: 8
- ✓ 10BASE-T, 100BASE-T, 1000BASE-T
- ✓ MAC address table: 4000 entries Switching capacity: 16 Gbit/s
- ✓ Desktop
- ✓ AC Power supply included

Aprašymas

Speedy Gigabit Performance and Diversified Options
There are five models for GS1200v3 series, coming with non-PoE (GS1200-5/8) to connect to devices including PCs, NAS, and print servers, PoE capable (GS1200-5HP/8HP) to provide power to IP CAM, wall mounted AP and PoE standard devices, and fiber uplink (GS1200-10) for easily deployment in hallways to connect network devices on the same floor and link them back to the core network.

Easy Web Management
This Series of switch comes with a user-friendly web-based set-up interface that walks you through setup, configuration and management—including configuration backups and firmware upgrades—quickly and easily. Some advanced features such as Link aggregation, VLAN, IGMP Snooping can be configured just with a few simple clicks.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Smart PoE+ 802.3at Support

PoE models support the IEEE 802.3at PoE+ standard, providing a maximum of 30 watts per port (with a max total power budget of 68 watts) to supply power to PoE network devices like wireless APs, IP cameras and VoIP phones. Web GUI management enables you to monitor the power status on each port and/or reboot the network devices, as needed.

Silent and Light-Off Design

The fanless design ensures all-time silent operation to blend into noise-free working environments. Also, you can deactivate turn off the Ethernet port LEDs for distraction-free operation by switching to LED ECO mode.

Blend Seamlessly into Your Workspace

Place the compact GS1200v3 switch wherever it fits best—on your desk, mounted on the wall, or neatly under the table—without taking up valuable space. Its built-in IEEE 802.3az Energy Efficient Ethernet (EEE) technology automatically detects network traffic and dynamically adjusts power consumption to save energy during low activity periods.

Techninė specifikacija

Specifications	
Sandėlio grupė	Root/Electronics/Networks and communication/Switchers [+36][-359]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Power connector	DC-in jack
Network	
Networking standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
Port mirroring	Yes
Full duplex	Yes
Flow control support	Yes
Broadcast storm control	Yes
VLAN support	Yes
Virtual LAN features	Port-based VLAN
Data transmission	
MAC address table	4000 entries

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Switching capacity	16 Gbit/s
Forwarding rate	11.9 Mpps
Jumbo frames support	Yes
Jumbo frames	15
Packet buffer memory	0.192 MB
Security	
DHCP features	DHCP client
IGMP snooping	Yes
Password protection	Yes
Queue scheduling algorithms	Weighted Round Robin (WRR)
Multicast features	
Multicast support	Yes
Number of multicast groups filtered	128
Design	
Rack mounting	No
Stackable	No
Form factor	Desktop
Product colour	Grey
LED indicators	Yes
Performance	
Fanless	Yes
Mean time between failures (MTBF)	1266805 h
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	3.81 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 95%

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Storage relative humidity (H-H)	10 - 95%
Heat dissipation	13 BTU/h
Weight & dimensions	
Width	193 mm
Depth	85 mm
Height	26 mm
Weight	268 g
Certificates	
Certification	CE-LVD, BSMI CE, EAC, FCC, BSMI Class B
Matmenys ir svoris	
Matmenys (I × P × A)	11,00cm × 18,00cm × 10,00cm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903