

ICY BOX IB-HUB1742CR-C2PD USB 3.2 Gen 2 (3.1 Gen 2) Type-A + Type-C 10000 Mbit/ai Juoda

Gamintojas: **RAIDSONIC** · Modelis: **IB-HUB1742CR-C2PD** · EAN: **4250078174936** · Prekės kodas: **645847**



87,89 €

Kaina su PVM

Be PVM: **72,64 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Priimančioji sąsaja: USB 3.2 Gen 2 (3.1 Gen 2) Type-A + Type-C
- ✓ „USB Power Delivery“
- ✓ Lizdo sąsajos: USB 3.2 Gen 2 (3.1 Gen 2) Type-A, USB 3.2 Gen 2 (3.1 Gen 2) Type-C
- ✓ Integruotas kortelių skaitytuvas MicroSD (TransFlash), MicroSDHC, MicroSDXC, SD, SDHC, SDXC
- ✓ Portų kiekis: 11
- ✓ Juoda Aliuminis
- ✓ 10000 Mbit/ai



Aprašymas

11-in-1 USB Type-C® hub with card reader and PD

Multi-connectivity

Ideal for content creators, editors, and professionals who juggle multiple devices. With 11 ports, including two USB-C® and one USB-A at 10 Gbit/s, plus SD®/microSD® card readers at up to 104 MB/s, it handles all your connections with ease.

Durable aluminum build

Built with sturdy aluminum, the hub effectively manages heat while maintaining a clean, modern look. It's made to last and keeps your workspace both functional and stylish.

Power Delivery

Includes two USB-C® PD ports delivering up to 22 W each, or up to 45 W when one is used solo. The 100 W upstream port charges notebooks while the LED display helps manage power usage efficiently.

Real-time LED display

The built-in LED shows current power output in watts. It gives you clear, real-time visibility to monitor and adjust power distribution as needed.

Integrated cable with dual connection

An attached cable with a USB-C® to USB-A adapter makes switching between different host devices simple. Whether you're on a MacBook or a standard PC, it's ready to connect.

Operating system

Supports both Windows® and macOS®. Whether you're using USB-C® or USB-A, it connects easily without extra drivers.

All-round talent

An 11-port USB hub with two PD ports, real-time wattage display, card readers and an integrated USB-C®/A cable – perfect for power users running Windows® and macOS®.

Multi-connectivity

For content creators, editors, and professionals who manage multiple devices daily. It provides 11 ports, including two USB 3.2 Gen 2 Type-C® and one USB Type-A port, delivering speeds of up to 10 Gbit/s. It also features three USB 3.2 Gen 1 Type-A ports with BC 1.2 fast charging and integrated SD®/microSD® card readers with up to 104 MB/s for quick file transfers.

Durable aluminum build

Made from robust aluminum, this hub is designed for efficient heat dissipation. The sleek design makes it a reliable and stylish addition to any workspace. This durable construction allows long-term use and keeps temperatures in check during demanding tasks.

Power Delivery

The device is equipped with two dedicated USB Type-C® ports for PD, offering up to 22 watts each. One port can even provide up to 45 watts when used alone. The 100 W PD upstream port powers notebooks and devices, and the real-time LED wattage display helps you track power usage for optimal management.

Techninė specifikacija

Ryšys	
Portų kiekis	11
Priimančioji sąsaja	USB 3.2 Gen 2 (3.1 Gen 2) Type-A + Type-C
Lizdo sąsajos	USB 3.2 Gen 2 (3.1 Gen 2) Type-A, USB 3.2 Gen 2 (3.1 Gen 2) Type-C
USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius	3
USB 3.2 (3.1 1 kart.) C tipo prievadų skaičius	1
USB 3.2 2 kart. (3.1 2 kart.) A tipo prievadų skaičius	1
USB 3.2 2 kart. (3.1 2 kart.) C tipo prievadų skaičius	2
Integruotas kortelių skaitytuvas	Taip
Kortelių skaitytuvo anga	2
Suderinamos atminties kortelės	MicroSD (TransFlash), MicroSDHC, MicroSDXC, SD, SDHC, SDXC
Savybės	
Duomenų perdavimo sparta	10000 Mbit/ai
Produkto spalva	Juoda
Korpuso medžiaga	Aliuminis
„USB Power Delivery“	Taip
USB maitinimo tiekimas iki	100 W
LED indikatoriai	Taip
Kabelio tipas	Apvalusis kabelis
Pakeitimas neišjungus	Taip
Kabelio ilgis	0,6 m
„Plug and Play“ funkcija	Taip
Kilmės šalis	Kinija
Tinklas	
UASP palaikymas	Taip
Energijos valdymas	
Maitinimo tipas	USB/DC
Iėjimo įtampa	24 V
Įvesties srovė	3 A
Sistemos reikalavimai	

Palaikomos „Windows“ operacinės sistemos	Taip
Palaikomos MAC operacinės sistemos	Taip
Palaikoma operacinė sistema „Linux“	Taip
Svoris ir matmenys	
Plotis	47 mm
Ilgis	160 mm
Aukštis	17 mm
Svoris	183 g
Pakuotės duomenys	
Kiekis pakuotėje	1 vnt
Paketo svoris	726 g
Pakuotės tipas	„Box“
Pakuotės turinys	
Kintamosios srovės adapteris	Taip
Instrukcija	Taip
Kitos savybės	
Lustų rinkinys	GL3590+AW3410*3+RM1211+FL7102

Dokumentai ir vaizdo įrašai

- › Naudojimo instrukcija
- › Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

RaidSonic Technology GmbH

Kurt-Fischer-Strasse 50, D-22926 Ahrensburg, DE

icybox.de

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt