

Microconnect B-FTP605W networking cable White 5 m Cat6 F/UTP (FTP)

Gamintojas: MICRO CONNECT · Modelis: B-FTP605W · EAN: 5712505707814 · Prekės kodas: 645892



12,90 €

Kaina su PVM

Be PVM: 10,66 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ To order a full box, please select the following quantity: 40 pcs.
- ✓ F/UTP Shielding, protects again EMI (Electromagnetic interference)
- ✓ with Latch Protection
- ✓ with slimline strain relief, with gold plated PINS
- ✓ high and low interference protections
- ✓ mechanical durability for vibrations

Aprašymas

CAT6 cables enables a convenient and reliable connection from one network device, such as switch, modem or router, to another or to the infrastructure at large through a patch panel, keystone jack or wall outlet. This cable are also used a lot in small office and home network and entertainment applications. These cables are tested up to 250Mhz (CAT6 standard) and are backwards compatible with CAT5e and CAT5 cables. They are produced with latch protection, which prevents the connector do be damaged when you install the cable through an installation with very less space. Furthermore this cable is manufactured with shielding. This protects against both EMI (electromagnetic interference). EMI can cause crosstalk between circuits, resulting in degradation of data, increased errors and slower transmission rates, but by using this shielded cable you will avoid this problem.

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Network > Network Adapters [+1948][-605]

Features

Cable length

5 m

Cable standard

Cat6

Cable shielding	F/UTP (FTP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	White
Connector 1 gender	Male
Connector 2 gender	Male
Jacket material	Polyvinyl chloride (PVC)
Conductor type	Stranded
Conductor material	Copper-Clad Aluminium (CCA)
AWG wire size	26
Data transfer rate	10000 Mbit/s
Frequency	250 MHz
Plug and Play	Yes
Certificates	
Compliance certificates	RoHS
Weight & dimensions	
Outer diameter	5.6 mm
Weight	100 g
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	
Package width	156 mm
Package depth	149 mm
Package height	38 mm
Package weight	144 g
Logistics data	
Harmonized System (HS) code	84733080
Other features	
Technical features	Kink Protection, strain relief and Latch Protection