InLine 32305O tinklo komutatorius Gigabit Ethernet (10/100/1000) Juoda

Gamintojas: **INLINE** · Modelis: **32305O** · EAN: **4043718298099** · Prekės kodas: **647297**



35,90 €

Kaina su PVM

Be PVM: **29,67 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 5
- ✓ Cat3, Cat4, Cat5, Cat5e, Cat6, Cat6+, Cat6a, Cat6e, Cat7, Cat7e, Cat8, Cat8.1 10BASE-T, 100BASE-T, 1000BASE-T
- ✓ Adreso lentelės dydis: 4000 įrašai Perjungimo pajėgumas: 1 Gbit/s
- ✓ Pridėtas maitinimo šaltinis







Aprašymas

Easy network distribution: The switch enables the reliable connection of up to five network-compatible devices via Ethernet and facilitates the creation of structured networks without configuration effort.
Stable continuous operation: The fanless metal housing supports silent operation and is suitable for continuous use in sensitive environments.
Automatic adaptation: All ports automatically detect speed and duplex mode and automatically adapt to connected devices.
Reliable data transmission: The store-and-forward process ensures that data packets are checked and forwarded correctly.
Flexible installation: Suitable for use on the desk or for wall mounting thanks to pre-punched mounting holes on the underside of the device.

The InLine® Gigabit network switch with five ports is used for the reliable expansion of existing networks. It enables the simple connection of several Ethernet devices via standard patch cables with a length of up to 100 m. Plug-and-play operation means that no configuration is required. The automatic negotiation of the transmission speed and Auto MDI/MDIX support fast and error-free commissioning.
The robust metal housing protects the internal electronics and supports stable continuous operation. Thanks to the fanless design, the switch

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

operates completely silently. The store-and-forward transmission method ensures controlled forwarding of data packets and contributes to reliable network communication.
Thanks to its support of common Ethernet standards, the switch can be easily integrated into existing network structures. The compact design and the option of wall mounting allow for flexible placement even where space is limited.

IEEE802.3i 10Base-T
IEEE802.3u 100Base-TX
IEEE802.3ab 1000Base-T
CSMA/CD
TCP/IP
IEEE802.3x flow control in full-duplex mode
Backpressure in half-duplex mode
MAC address table: 4K
Forwarding rate: 1488000 pps per port
Backbone bandwidth: 1 Gb/s
RJ45 ports with Auto MDI/MDIX
Supported cable types: UTP Cat.5, Cat.5e or higher
Operating temperature: 0 °C to 60 °C
Storage temperature: -10 °C to 70 °C
Operating humidity: 10% to 90% non-condensing

Techninė specifikacija

Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	5
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Network	
Networking standards	IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6, Cat6+, Cat6a, Cat6e, Cat7, Cat7e, Cat8, Cat8.1
Full duplex	Yes
Half duplex	Yes
Flow control support	Yes
Auto MDI/MDI-X	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto-negotiation	Yes
MAC address auto-learning supported	Yes
Data transmission	
MAC address table	4000 entries
Switching capacity	1 Gbit/s
Forwarding rate	1.488 Mpps
Store-and-forward	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Transmission method	Store-and-forward
Design	
Product colour	Black
LED indicators	Link, Power
Performance	
Maximum data transfer rate	1000 Mbit/s
Power	
Power supply included	Yes
DC input voltage	5 V
Input current	1 A
Other features	
Dimensions (WxDxH)	93 x 2.89 x 68 mm
Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Ethernet LAN (RJ-45) ports	5
Operational conditions	
Operating temperature (T-T)	0 - 60 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	93 mm
Depth	2.89 mm
Height	68 mm
Weight	2.5 kg
Packaging data	
Package width	110 mm
Package depth	160 mm
Package height	65 mm
Package weight	162 g

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Gamintojo ir saugos informacija

GAMINTOJAS

InLine

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt