

Canon EOS RP MILC Body 26.2 MP CMOS 6240 x 4160 pixels Black

Gamintojas: **CANON** · Modelis: **3380C003** · EAN: **4549292132151** · Prekės kodas: **647317**



785,90 €

Kaina su PVM

Be PVM: **649,50 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ MILC Body 26.2 MP CMOS Touchscreen Black
- ✓ Image stabilizer
- ✓ Digital zoom: 10x
- ✓ Face tracking
- ✓ ISO sensitivity (min): 100 ISO sensitivity (max): 40000 Fastest camera shutter speed: 1/4000 s Slowest camera shutter speed: 0.00025 s ± 3EV (1/2EV; 1/3EV step)
- ✓ Video recording 3840 x 2160 pixels 4K Ultra HD
- ✓ Built-in microphone PictBridge USB Type-C HDMI Bluetooth Wi-Fi
- ✓ Lithium-Ion (Li-Ion) 7.2 V



Techninė specifikacija

Specifications

Sandėlio grupė

Kamera > Digitalkameras [+86][[-33]

Picture quality

Camera type

MILC Body

Megapixel (approx.)

26.2 MP

Sensor type

CMOS

Maximum image resolution	6240 x 4160 pixels
Still image resolution(s)	3:2 ratio (L, RAW, C-RAW) 6240x4160, (M1) 4160x2768, (S1) 3120x2080, (S2) 2400x1600 1.6x (crop) (L) 3888x2592, (S2) 2400x1600 4:3 ratio (L) 5536x4160, (M1) 3680x2768, (S1) 2768x2080, (S2) 2112x1600 16:9 ratio (L) 6240x3504, (M1) 4160x2336, (S1) 3120x1752, (S2) 2400x1344 1:1 ratio (L) 4160x4160, (M1) 2768x2768, (S1) 2080x2080, (S2) 1600x1600
Image stabilizer	Yes
Image formats supported	JPEG, Raw
Supported aspect ratios	1:1, 2:3, 3:2, 3:4, 4:3, 16:9
Total megapixels	27.1 MP
Image sensor size (W x H)	35.9 x 24 mm
Sensor format	Full-frame
Lens system	
Digital zoom	10x
Focal length range	1 mm
Focusing	
Focus adjustment	Auto/Manual
Auto focusing (AF) modes	Contrast Detection Auto Focus, Multi Point Auto Focus, Single Auto Focus
Auto Focus (AF) object detection	Face
Face tracking	Yes
Auto Focus (AF) points	4779
Auto Focus (AF) points selection	Auto, Manual
Auto Focus (AF) lock	Yes
Exposure	
ISO sensitivity (min)	100
ISO sensitivity (max)	40000
Light exposure modes	Aperture priority AE, Auto, Manual, Shutter priority AE
Light exposure correction	± 3EV (1/2EV; 1/3EV step)
Light metering	Centre-weighted, Evaluative (Multi-pattern), Highlight-weighted, Spot
ISO sensitivity	100, 40000
Light exposure control	Program AE
Auto Exposure (AE) lock	Yes
Number of measurement zones	384
Shutter	
Fastest camera shutter speed	1/4000 s
Slowest camera shutter speed	0.00025 s

Camera shutter type	Electronic
Flash	
Flash modes	Auto, Flash off, Flash on, High-speed synchronization, Manual, Normal, Red-eye reduction, Second curtain synchro, Slave
Flash exposure lock	Yes
Flash exposure compensation	Yes
Flash exposure correction	±3EV (1/2; 1/3 EV step)
Pre-flash	Yes
Shoe mounting point	No
Video	
Video recording	Yes
Maximum video resolution	3840 x 2160 pixels
HD type	4K Ultra HD
Video resolutions	1280 x 720,1920 x 1080,3840 x 2160
Video recording time	30 min
Motion JPEG frame rate	60 fps
Resolution at capture speed	3840x2160@25fps
Video formats supported	MPEG4
Audio	
Built-in microphone	Yes
Audio system	stereo
Memory	
Compatible memory cards	SDHC, SDXC
Memory slots	1
Display	
Display	LCD
Touchscreen	Yes
Display diagonal	7.62 cm (3")
Display diagonal (metric)	7.5 cm
Display resolution	1040000 dot
Flip-out screen	Yes
Vari-angle LCD display	Yes
Field of view	100%
Viewfinder	
Viewfinder type	Electronic

Magnification	0.7x
Viewfinder screen size	0.39"
Viewfinder resolution (approx.)	236000 pixels
Ports & interfaces	
PictBridge	Yes
USB version	2
HDMI	Yes
Connection to PC	Yes
USB connector	USB Type-C
Microphone in	Yes
USB port	Yes
Network	
Bluetooth	Yes
Wi-Fi	Yes
Near Field Communication (NFC)	No
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Camera	
White balance	Cloudy, Custom modes, Daylight, Flash, Fluorescent, Manual, Tungsten
Scene modes	Children, Close-up (macro), Night, Night landscape, Night portrait, Panorama, Sports, Sunset, Twilight
Shooting modes	Aperture priority, Auto, Manual, Program, Shutter priority
Photo effects	Black&White, Grey, Neutral, Vivid
Self-timer delay	2,10 s
Tripod mounting supported	Yes
Contrast adjustment	Yes
Brightness adjustment	Yes
Playback zoom (max)	10x
Histogram	Yes
Live view	Yes
On Screen Display (OSD) languages	BEL, Simplified Chinese, Traditional Chinese, Croatian, Czech, Danish, German, Dutch, English, Spanish, Finnish, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Swedish, Thai, Turkish, Ukrainian
Camera file system	Raw
Multi-shot	Yes
Built-in processor	Yes
Image processor	DIGIC 8

Windows operating systems supported	Windows 10, Windows 10 Pro, Windows 10 x64, Windows 7, Windows 8.1
Design	
Product colour	Black
Dustproof	Yes
Splash proof	Yes
Material	Fiberglass, Polycarbonate (PC)
Battery	
Battery technology	Lithium-Ion (Li-Ion)
Battery voltage	7.2 V
Battery life (CIPA standard)	250 shots
Battery capacity	1040 mAh
Number of batteries supported	1
Rechargeable battery	Yes
Battery level indicator	Yes
Power	
USB Type-C charging port	Yes
USB Type-C required charging power (min)	7.5 W
USB Type-C required charging power (max)	7.5 W
System requirements	
Mac compatibility	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 85%
Storage relative humidity (H-H)	0 - 85%
Recommended humidity operating range	0 - 85%
Maximum operating temperature range (T-T)	0 - 40 °C
Recommended operating temperature range (T-T)	0 - 40 °C
Weight & dimensions	
Width	132.5 mm
Depth	70 mm
Height	85 mm
Weight	440 g
Weight (including battery)	485 g

Packaging data

Package width	282 mm
Package depth	225 mm
Package height	151 mm
Package weight	1.22 kg

Packaging content

AC adapter included	Yes
Neck strap included	Yes
Shoulder strap	Yes
Power cord included	Yes
Battery charger included	Yes
Batteries included	Yes
Lens cap included	Yes
Camera flash included	Yes
User guide	Yes

Other features

Dimensions (WxDxH)	133 x 85 x 70 mm
Built-in flash	Yes
Aperture priority AE	Yes
Auto exposure	Yes
Battery pack	Yes
Display tilting	Yes
Number of HDMI outputs	1
Shutter priority AE	Yes
USB 2.0 connectors	1
Video compression formats	MPEG4
Supplied battery type	LP-E17

Technical details

Display brightness control	Yes
Package weight	1.22 kg
Batteries	LP-E17