

InLine Dual 10-Gigabit network card, 2x RJ45 10Gb/s, PCIe x8, incl. LP bracket

Gamintojas: **INLINE** · Modelis: **51128A** · EAN: **4043718333288** · Prekės kodas: **647604**



128,90 €

Kaina su PVM

Be PVM: **106,53 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Internal
- ✓ Host interface: PCIe
- ✓ Output interface: RJ-45
- ✓ 10 Gbit/s



Aprašymas

Dual-port network card with two 10GbE RJ45 ports for maximum performance
Intel X540 chipset for maximum reliability and compatibility
PCIe x8 interface in accordance with revision 2.1 for professional IT environments
Supports VLAN, link aggregation, iSCSI boot and other protocols
Backwards compatible with 1000Base-T networks

The InLine® Dual 10 Gigabit network card offers two high-performance 10GBASE-T ports for the highest data transfer rates in professional networks. It is ideal for servers, workstations and demanding applications with high bandwidth requirements.

With the integrated Intel X540 chipset, the card ensures maximum stability and is compatible with numerous network technologies. These include VLAN tagging, IEEE802.3ad Link Aggregation Control Protocol (LACP), PXE boot as well as iSCSI and FCoE support.

Thanks to the PCIe x8 interface (Rev. 2.1), the card can be flexibly integrated into modern IT infrastructures. Backwards compatibility with 1000Base-T enables a smooth transition to 10GbE networks.

Technical specifications:

Chipset: Intel X540

Interface: PCI Express x8, Revision 2.1

Ports: 2x RJ45 10Gb/s (10GBASE-T)

Network protocols: TCP/IP, UDP/IP, IPSec, iSCSI

Supported standards: IEEE 802.3an, IEEE 802.3ab, IEEE 802.1Q, IEEE 802.1P, IEEE 802.3ad

Functions: VLAN, LACP, Layer 2 prioritization, PXE, FCoE, iSCSI boot

Backwards compatible with 1000Base-T

Compatible operating systems: Windows 7 or newer, Server 2008 or newer, Linux kernel ≥ 2.6

Operating temperature: 0° C – 55° C

Storage temperature: -40° C – 70° C

Humidity: 10% - 90% non-condensing

Operating temperature: 0° C – 55° C

Storage temperature: -40° C – 70° C

Humidity: 10% - 90% non-condensing

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Ports & interfaces	
Host interface	PCIe
Output interface	RJ-45
Host interface gender	Male
Expansion card standard	PCIe 2.1
Design	
Internal	Yes
Cooling type	Passive
Country of origin	China
Features	
Data transfer rate (max)	10 Gbit/s
System requirements	
Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows Vista
Linux operating systems supported	Kernel 2.6, Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4, Linux Kernel 5.10, Linux Kernel 5.11, Linux Kernel 5.12, Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2
Server operating systems supported	Windows Server 2008, Windows Server 2012, Windows Server 2013, Windows Server 2016, Windows Server 2019, Windows Server 2022
Weight & dimensions	

Width	160 mm
Depth	2.43 mm
Height	120 mm
Weight	2 kg
Packaging data	
Mounting brackets included	Yes
Package width	150 mm
Package depth	175 mm
Package height	30 mm
Package weight	161 g
Other features	
Dimensions (WxDxH)	160 x 2.43 x 120 mm