

# InLine 66659N network card Fiber 1000 Mbit/s

Gamintojas: **INLINE** · Modelis: **66659N** · EAN: **4043718349180** · Prekės kodas: **647828**



**89,90 €**

Kaina su PVM

Be PVM: **74,30 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Wired
- ✓ USB 3.2 Gen 1 (3.1 Gen 1) Fiber
- ✓ 1000 Mbit/s
- ✓ Chipset: Realtek RTL8153



## Aprašymas

**Modular fiber optic connection via USB-A:** Flexible use through SFP port for different transceivers – ideal for changing network architectures.

**Gigabit performance with energy efficiency:** Supports up to 1.000 Mb/s and reduces power consumption thanks to IEEE802.3az.

**Compatible with many operating systems:** Broad support for Windows, macOS and Linux enables versatile integrations.

**Loss-free data transmission:** On-chip buffer, flow control and checksum offload ensure reliable and fast communication.

**Ideal for industrial and IT environments:** Works interference-free in electromagnetically sensitive areas and over long distances.

The InLine® USB-A to SFP Gigabit Fiber network adapter is the ideal solution for professional network environments that rely on flexibility, reliability and compatibility. With its modular SFP port, different fiber optic transceivers (e.g. SX, LX) can be used – perfect for different ranges and infrastructures. The adapter supports network speeds of up to 1,000 Mb/s via the USB-A port and is therefore ideal for fast, stable connections with low latency.

The adapter scores particularly well in industrial applications, data centers or IT integration with functions such as IEEE802.3az for energy saving, flow control to prevent packet loss and QoS capability for prioritized data transmission. The integrated support for VLAN tagging and automatic detection of cable types also ensures easy integration into existing systems.

Thanks to the broad operating system support for Windows, macOS and Linux, the device can be used in a variety of ways - for example for

temporary network connections, notebooks in service management or for permanent integration into rack solutions. The integrated on-chip buffer and the extensive offload functions reduce the load on the system and ensure loss-free data transfer, even under high load.

Network protocols: IEEE802.3 / 802.3u / 802.3ab

VLAN / Prioritization: IEEE802.1Q, Layer 2 Priority

Jumbo Frames: Up to 9K

Power saving functions: Power Down / Link Down / LPM

Skew/polarity correction

Crossover detection (Auto-MDI/MDI-X)

Chip set: Realtek RTL8153

## Techninė specifikacija

| Specifications                      |                                                                  |
|-------------------------------------|------------------------------------------------------------------|
| Sandėlio grupė                      | Server, Storage & Network > Network Adapters [+1948][-605]       |
| Ports & interfaces                  |                                                                  |
| Connectivity technology             | Wired                                                            |
| Host interface                      | USB                                                              |
| Interface                           | Fiber                                                            |
| Fiber ports quantity                | 1                                                                |
| Fiber optic connector               | SFP                                                              |
| USB connector form factor           | Straight                                                         |
| USB version                         | 3.2 Gen 1 (3.1 Gen 1)                                            |
| Network                             |                                                                  |
| Maximum data transfer rate          | 1000 Mbit/s                                                      |
| Networking standards                | IEEE 802.3az, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1Q |
| Jumbo frames support                | Yes                                                              |
| Jumbo frames                        | 9000                                                             |
| VLAN support                        | Yes                                                              |
| Design                              |                                                                  |
| Internal                            | No                                                               |
| Chipset                             | Realtek RTL8153                                                  |
| Country of origin                   | Taiwan                                                           |
| Power                               |                                                                  |
| USB powered                         | Yes                                                              |
| System requirements                 |                                                                  |
| Windows operating systems supported | Yes                                                              |
| Mac operating systems supported     | MacOS                                                            |

|                                   |                  |
|-----------------------------------|------------------|
| Linux operating systems supported | Yes              |
| Weight & dimensions               |                  |
| Width                             | 45 mm            |
| Depth                             | 270 mm           |
| Height                            | 18 mm            |
| Weight                            | 47 g             |
| Packaging data                    |                  |
| Package type                      | Hanging box      |
| Package width                     | 125 mm           |
| Package depth                     | 175 mm           |
| Package height                    | 30 mm            |
| Package weight                    | 111 g            |
| Technical details                 |                  |
| Compliance certificates           | TÜV mark, CE     |
| Other features                    |                  |
| Dimensions (WxDxH)                | 45 x 270 x 18 mm |
| Package volume                    | 6500 cm³         |