

InLine 2 Port USB 3.0 Host Controller Card with SATA Auxiliary Power Port PCIe

Gamintojas: **INLINE** · Modelis: **76666L** · EAN: **4043718203079** · Prekės kodas: **647961**



34,90 €

Kaina su PVM

Be PVM: **28,84 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Complies with PCI Express Base Specification Revision 2.0
- ✓ Complies with Universal Serial Bus 3.0 specification Revision 1.0
- ✓ Backward compatible to USB 2.0 and PCI-Express 1.0
- ✓ Supports the following data transfer rate: USB 2.0 mode up to 480 Mb/s, USB 3.0 mode up to 5 Gb/s
- ✓ Max. 5V/900mA power output to each USB 3.0 Port
- ✓ 4-pin power connector for extra power which must be connected with the card
- ✓ Supports Windows 8, Windows 7/Vista/XP 32/64-bit, Server 2008 32/64-bit
- ✓ Eltron EJ168 Chipset
- ✓ incl. low-profile bracket



Aprašymas

Note:We refer to the website 'Drivers-Download' in the operating instructions included in the contents of delivery; this website has no connection with our company and is now being misused for phishing purposes.

We therefore strongly advise against using this website!

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Ports & interfaces	
Host interface	PCIe
Output interface	USB 3.2 Gen 1 (3.1 Gen 1)
Expansion card form factor	Low-profile
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
Design	
Internal	Yes
Features	
Data transfer rate (max)	5 Gbit/s
System requirements	
Windows operating systems supported	Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Server operating systems supported	Windows Server 2008, Windows Server 2008 x64
Technical details	
Compliance certificates	RoHS
Weight & dimensions	
Depth	1.27 mm
Weight	65 g
Packaging data	
Package width	144 mm
Package depth	179 mm
Package height	40 mm
Package weight	65 g
Package volume	1000 cm³
Other features	
Data transfer rate	5000 Mbit/s