

InLine Patch Cable S/FTP PiMF Cat.6A halogen free 500MHz white 1m

Gamintojas: **INLINE** · Modelis: **76811W** · EAN: **4043718189878** · Prekės kodas: **647976**

15,90 €

Kaina su PVM

Be PVM: **13,14 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Assignment according to TIA/EIA 568B2.1
- ✓ cable construction S/FTP (PiMf) 4x2xAWG26/7
- ✓ overall braided shield with paired foil shield
- ✓ Cable sheath halogen free, LSZH, conform to standards IEC 60332-1-2, IEC 60754-1, IEC 60754-2, IEC 61034 IEC332-1
- ✓ plug RJ45 (8P8C) with 50μ" gold plated contacts and with special design and latch protection
- ✓ blue colored plug for easy distinction
- ✓ For Gigabit and 10 Gigabit applications
- ✓ to 500MHz: 100% Cat.6 test and 100% Cat.6A test (Fluke Channel Link Test) including the attached test protocol and serial number
- ✓ in reclosable PE bag with EAN code

Aprašymas

Patch cable in the highest quality for a professional cabling in Gigabit and 10 Gigabit range, for use in data centers and server racks

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Network > Network Adapters [+1948][-605]

Features

Cable length

1 m

Cable standard

Cat6a

Cable shielding	S/FTP (S-STP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	White
Connector 1 gender	Male
Connector 2 gender	Male
Jacket material	Low smoke zero halogen (LSZH)
Conductor material	Copper
Cabling technology	10/100/1000Base-T(X)
Ethernet interface type	10 Gigabit Ethernet
AWG wire size	26/7
Data transfer rate	10000 Mbit/s
Frequency	500 MHz
Sustainability	
Doesn't contain	Halogen
Certificates	
Certification	IEC 60332-1-2, IEC 60754-1, IEC 60754-2, IEC 61034 IEC332-1
Weight & dimensions	
Width	12 mm
Depth	1000 mm
Height	15 mm
Weight	45 g
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	
Package width	90 mm
Package depth	110 mm
Package height	20 mm
Package weight	51 g
Package volume	200 cm ³
Package type	Polybag
Other features	
Dimensions (WxDxH)	12 x 1000 x 15 mm