

TP-Link Archer C50 wireless router Fast Ethernet Dual-band (2.4 GHz / 5 GHz) White

Gamintojas: **TP-LINK** · Modelis: **ARCHER C50 V3** · EAN: **8592978083649** · Prekės kodas: **649328**



54,90 €

Kaina su PVM

Be PVM: **45,37 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Tabletop router White
- ✓ Dual-band (2.4 GHz / 5 GHz) Wi-Fi 5 (802.11ac) 867 Mbit/s
- ✓ Fast Ethernet
- ✓ Ethernet WAN
- ✓ Ethernet LAN (RJ-45) ports: 4
- ✓ Quality of Service (QoS) support



Aprašymas

- Supports 802.11ac standard - the next generation of Wi-Fi
- Simultaneous 2.4GHz 300Mbps and 5GHz 867Mbps connections for 1.2Gbps of total available bandwidth
- 2 dual band external antennas provide stable wireless connections and optimal coverage
- Easy network management at your fingertips with TP-LINK Tether

Fast Wireless Speed with 802.11ac

TP-LINK's Archer C50 comes with the next generation Wi-Fi standard – 802.11ac, 3 times faster than wireless N speeds and delivering a combined wireless data transfer rate of up to 1.2Gbps. With 300Mbps over the 2.4GHz band and 867Mbps wireless speeds over the crystal clear 5GHz band, the Archer C50 is the superior choice for seamless HD streaming, online gaming and other bandwidth-intensive tasks.

1.2Gbps Dual Band Connections for Lag-Free Work and Entertainment

The Archer C50 operates over both the 2.4GHz and 5GHz bands, ensuring amazing wireless performance. Simultaneous Dual Band offers you the flexibility of two dedicated networks – with multiple times the bandwidth for your needs. Simple tasks like sending e-mails or web browsing can be handled by the 2.4GHz band while bandwidth intensive tasks like online gaming or HD video streaming can be processed by the 5GHz band – all at the same time.

2 External Antennas for Optimal Coverage

With 2 external antennas combined with high quality antenna technology, you can maintain high speeds across greater distances. This provides you with optimal wireless coverage and reliability from anywhere in your large home or office.

USB Port for Storage and Sharing

With USB 2.0 port, you can share a printer locally and files & media with networked devices or remotely via FTP server.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server/Storage/Network > Access Points/Routers [+1151][-307]
WAN connection	
Ethernet WAN	Yes
Wireless LAN features	
Wi-Fi band	Dual-band (2.4 GHz / 5 GHz)
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)
WLAN data transfer rate (max)	867 Mbit/s
Wi-Fi standards	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)
WLAN data transfer rate (first band)	867 Mbit/s
WLAN data transfer rate (second band)	300 Mbit/s
Network	
Ethernet LAN	Yes
Ethernet LAN interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Cabling technology	10/100Base-T(X)
Port forwarding	Yes
Receiver sensitivity	5GHz: 11a 54M: -76dBm 11ac VHT20 MCS8: -70dBm 11ac VHT40 MCS9: -65.5dBm 11ac VHT80 MCS9: -61.5dBm 2.4GHz: 11g 54M: -76dBm 11n HT20 MCS7: -74dBm 11n HT40 MCS7: -71d
Mobile network	
3G	No
4G	No

Ports & interfaces

Ethernet LAN (RJ-45) ports	4
USB port	No
DC-in jack	Yes

Management features

Quality of Service (QoS) support	Yes
Reset button	Yes

Security

Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
Firewall	Yes
Firewall security	Domain Filter, IP Address Binding, MAC Address Binding
Stateful Packet Inspection (SPI)	Yes
DoS attack prevention	Yes
Filtering	Yes
MAC address filtering	Yes
IP address filtering	Yes
DMZ support	Yes

Protocols

DHCP client	Yes
DHCP server	Yes
Supported network protocols	IPv4 / IPv6

Design

Product type	Tabletop router
Product colour	White
On/off switch	Yes

Certificates

Certification	CE, FCC, RoHS
---------------	---------------

Packaging content

Cables included	LAN (RJ-45)
AC adapter included	Yes
Quick start guide	Yes

Antenna

Antenna design	External
Antennas quantity	4

Power

Power source type	DC
Output voltage	9 V
Output current	0.85 A

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

System requirements

Windows operating systems supported	Yes
Linux operating systems supported	Yes
Mac operating systems supported	Yes
Mac compatibility	Yes

Weight & dimensions

Width	182.9 mm
Depth	123.5 mm
Height	32.1 mm