

ATEN CN9850-AT-G KVM switch Black

Gamintojas: **ATEN** · Modelis: **CN9850-AT-G** · EAN: **4710469349324** · Prekės kodas: **650422**



850,90 €

Kaina su PVM

Be PVM: **703,22 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Black
- ✓ Keyboard port type: USB Mouse port type: USB Video port type: HDMI
- ✓ 4K Ultra HD 4096 x 2160 pixels
- ✓ Housing material: Metal
- ✓ DC 10.07 W



Aprašymas

The CN9850 KVM over IP Switch allows for remote access to video, audio, and virtual media of a PC or workstation, and features HDMI high-definition video with resolutions of up to 4K DCI (4096 x 2160) @ 30 Hz at both the local and remote consoles. Built with an advanced FPGA graphics processor, the CN9850 offers better image and video quality to enhance the user experience, while also meeting the RS-232 standards for serial control.

For user-friendly operation, a mini USB port on the front panel is designed as a Laptop USB Console (LUC) port for connection to a laptop, which allows the user to access the PC / server for easy routine maintenance without requiring an additional monitor, keyboard, and mouse.

To seamless stable connectivity, the CN9850 is equipped with dual LAN and dual power functionality to keep operations in the server room smooth and efficient. Its power status detection function automatically sends out event notifications when the devices are offline (e.g. power failure) for device status monitoring. Moreover, the CN9850 features a 5-pin Relay / DI (digital input) terminal block allowing for remote reboot of the local

server, and receiving digital input from a connected input/alarm device for notification of critical events.

For ease of remote management, the CN9850 WebClient Viewer supports remote desktop access without additional software applications. The HDMI 4K KVM over IP Switch provides a webbased GUI for remote access and management. In addition, a unified multi-language interface can minimize user training time and increase productivity.

The CN9850 is ideal for data centers, server rooms, and control rooms for remote access management in industries with requirements for high-quality images and multitasking, such as global organizations and companies with several office locations where it can function as a bridge between local and remote workplaces.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Ports & interfaces	
Keyboard port type	USB
Mouse port type	USB
Video port type	HDMI
Console ports	HDMI, USB A
HDMI ports quantity	1
USB 2.0 Type-B ports quantity	1
Console USB ports quantity	2
Console HDMI ports quantity	1
USB connector type	Mini-USB B
PS/2 ports quantity	1
Serial port type	RJ-45
Serial ports quantity	2
Audio connections	Yes
Headphone outputs	2
Number of microphone inputs	2
DC-in jack	Yes
Performance	
HD type	4K Ultra HD
Maximum resolution	4096 x 2160 pixels
Video bandwidth	30 Hz
Design	
Product colour	Black
Housing material	Metal

LED indicators	Power
Display	
Built-in display	No
Power	
Power source	DC
Output voltage	5 V
Power consumption (typical)	10.07 W
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	150.5 mm
Depth	200 mm
Height	28.4 mm
Weight	840 g
Packaging data	
Package width	98 mm
Package depth	325 mm
Package height	210 mm
Package weight	1.69 kg
Packaging content	
Cables included	KVM, USB
Logistics data	
Harmonized System (HS) code	84718000
Master (outer) case width	342 mm
Master (outer) case length	512 mm
Master (outer) case height	232 mm
Master (outer) case gross weight	9.1 kg
Country of origin	Taiwan