

ATEN 8-Port USB - PS/2 VGA KVM Switch

Gamintojas: **ATEN** · Modelis: **CS1308** · EAN: **4710423775916** · Prekės kodas: **650532**



279,90 €

Kaina su PVM

Be PVM: **231,32 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ One USB-PS/2 console controls 8 computers; Cascade up to 2 levels - control up to 64 computers
- ✓ Broadcast mode - operations simultaneously performed on all selected computers, software installation and upgrading, system wide shutdown, etc
- ✓ Computer selection via front panel pushbuttons, hotkeys and multilingual on-screen display (OSD) menu
- ✓ Video DynaSync™ - Exclusive ATEN technology eliminates boot-up display problems and optimizes resolution when switching between ports



Aprašymas

The CS1308 is a 8-Port USB-PS/2 KVM switch (Dual Interface). You're able to control up to 64 Computers from a single console (keyboard, mouse, and monitor).

8 additional switches can be cascaded (2-Level) that's why the total number of connected computers can be up to 64 computers, that can be controlled from a single keyboard-monitor-mouse console. The switch supports both USB and PS/2 connections for the console and Computer/PC/Server (Dual Interface).

1x CS1308 KVM Switch with Rack Mount Kit

1x LIN5-27X6-U21G Console cable

1x Firmware Upgrade cable

1x Foot Pad set (4 pads)

1x 0AD8-1605-24M1 Power Adapter

1x User Instructions

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Ports & interfaces	
Number of computers controlled	64
Keyboard port type	USB, PS/2
Mouse port type	USB, PS/2
Video port type	VGA
Console ports	VGA (D-Sub)
VGA (D-Sub) ports quantity	8
DC-in jack	Yes
Performance	
HD type	QXGA
Maximum resolution	2048 x 1536 pixels
Scan interval	1,255 s
DDC2B support	Yes
Firmware upgradeable	Yes
Design	
Rack mounting	Yes
Product colour	Black
Rack capacity	1U
Housing material	Metal
Cascadable	Yes
Push button	Yes
Hot keys	Yes
Display	
Built-in display	No
Power	
Power source	DC
Input voltage	5.3 V
Power consumption (typical)	5 W
System requirements	
Windows operating systems supported	Yes
Linux operating systems supported	Yes

Mac operating systems supported	Yes
Other operating systems supported	Yes
Sustainability	
Compliance certificates	RoHS
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	161.3 mm
Depth	437.2 mm
Height	44 mm
Weight	1.89 kg
Packaging data	
Package width	116 mm
Package depth	540 mm
Package height	233 mm
Package weight	2.69 kg
Packaging content	
Quick installation guide	Yes
AC adapter included	Yes
Rack mount kit	Yes
Rubber feet	Yes
Logistics data	
Master (outer) case net weight	6.72 kg
Harmonized System (HS) code	85176200
Master (outer) case width	375 mm
Master (outer) case length	565 mm
Master (outer) case height	258 mm
Master (outer) case gross weight	8.7 kg
Products per master (outer) case	3 pc(s)