

# **ATEN 8-Port USB - PS/2 VGA KVM Over IP Switch with USB Peripheral port**

Gamintojas: **ATEN** · Modelis: **CS1708i** · EAN: **4710423776715** · Prekės kodas: **650533**



## **788,90 €**

Kaina su PVM

Be PVM: **651,98 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## **Pagrindinės savybės**

- ✓ Superior video quality - up to 2048 x 1536; DDC2B for the local console; up to 1920 x 1200 @ 60Hz\*\* and 1600 x 1200 @ 60Hz / 24 bit color depth for remote sessions
- ✓ Supports TLS 1.2 data encryption and RSA 2048 bit certificates for secure user logins from a browser
- ✓ Panel array mode enables user to monitor multiple servers from single screen at the same time - each selected server's video output appears in a separate panel - users can easily select the number of panels to view



## **Aprašymas**

The CS1708i is an 8-port KVM switch in a 1U housing for convenient rack mounting. This device allows system administrators to access the attached servers both locally and over IP (LAN and/or WAN). CS1708i works platform independent and supports e.g. Windows, Linux, MAC, SUN

The special KVM cables and the Aten feature "Video DynaSync", makes sure that an optimal video resolution can be maintained. In addition it's easy to expand the KVM installation. By using Daisy Chain cables the number of accessible servers can be increased up to 128.

1x CS1708i KVM over IP Switch

1x 2L-5202P PS/2 KVM Cable

1x 2L-5202U USB KVM Cable

1x LIN5-27X6-U21G Console Cable

- 1x Firmware Upgrade Cable
- 1x Mounting Kit
- 1x Foot Pad Set (4 pcs)
- 1x 0AD8-1605-24M1 Power Adapter
- 1x User Instructions

Techninė specifikacija

| Specifications                 |                                                     |
|--------------------------------|-----------------------------------------------------|
| Sandėlio grupė                 | Server, Storage & Netzwerk > Switches [+1398][-565] |
| Ports & interfaces             |                                                     |
| Number of computers controlled | 128                                                 |
| Keyboard port type             | USB, PS/2                                           |
| Mouse port type                | USB, PS/2                                           |
| Video port type                | VGA                                                 |
| Console ports                  | VGA (D-Sub)                                         |
| Console USB ports quantity     | 1                                                   |
| USB connector type             | USB Type-A                                          |
| DC-in jack                     | Yes                                                 |
| Network                        |                                                     |
| Ethernet LAN                   | Yes                                                 |
| Ethernet LAN (RJ-45) ports     | 1                                                   |
| Security algorithms            | 128-bit RC4, RSA, SSL/TLS                           |
| Performance                    |                                                     |
| HD type                        | QXGA                                                |
| Maximum resolution             | 2048 x 1536 pixels                                  |
| Scan interval                  | 1,255 s                                             |
| DDC2B support                  | Yes                                                 |
| Hot-Plug support               | Yes                                                 |
| Daisy chain                    | Yes                                                 |
| Number of users                | 32 user(s)                                          |
| Firmware upgradeable           | Yes                                                 |
| Design                         |                                                     |
| Rack mounting                  | Yes                                                 |
| Product colour                 | Black                                               |
| Rack capacity                  | 1U                                                  |
| Housing material               | Metal                                               |

|                                     |             |
|-------------------------------------|-------------|
| LED indicators                      | Yes         |
| Push button                         | Yes         |
| Hot keys                            | Yes         |
| Display                             |             |
| Built-in display                    | No          |
| On Screen Display (OSD)             | Yes         |
| Power                               |             |
| Power source                        | DC          |
| Input voltage                       | 5.3 V       |
| Power consumption (typical)         | 9.5 W       |
| System requirements                 |             |
| Windows operating systems supported | Yes         |
| Linux operating systems supported   | Yes         |
| Mac operating systems supported     | Yes         |
| Sustainability                      |             |
| Compliance certificates             | RoHS        |
| Operational conditions              |             |
| Operating temperature (T-T)         | 0 - 50 °C   |
| Storage temperature (T-T)           | -20 - 60 °C |
| Operating relative humidity (H-H)   | 0 - 80%     |
| Weight & dimensions                 |             |
| Width                               | 437.2 mm    |
| Depth                               | 159.6 mm    |
| Height                              | 44 mm       |
| Weight                              | 3.42 kg     |
| Packaging data                      |             |
| Package width                       | 116 mm      |
| Package depth                       | 540 mm      |
| Package height                      | 233 mm      |
| Package weight                      | 3.83 kg     |
| Packaging content                   |             |
| Cables included                     | DC, KVM     |
| Quick installation guide            | Yes         |
| Manual                              | Yes         |

|                                  |          |
|----------------------------------|----------|
| Software included                | Yes      |
| Rack mount kit                   | Yes      |
| Logistics data                   |          |
| Master (outer) case net weight   | 10.3 kg  |
| Harmonized System (HS) code      | 85176200 |
| Master (outer) case width        | 375 mm   |
| Master (outer) case length       | 565 mm   |
| Master (outer) case height       | 258 mm   |
| Master (outer) case gross weight | 12.1 kg  |
| Products per master (outer) case | 3 pc(s)  |