

ATEN 16-Port USB 3.0 4K DisplayPort KVM Switch

Gamintojas: **ATEN** · Modelis: **CS19216** · EAN: **4719264649264** · Prekės kodas: **650539**



1 792,91 €

Kaina su PVM

Be PVM: **1 481,74 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Superior video quality – up to 4K DCI (4096 x 2160 @ 60Hz) and built-in 2-port USB 3.1 Gen 1 hub with SuperSpeed 5 Gbps data transfer rates
- ✓ Cascadable to two levels – controls up to 256 computers
- ✓ Multi-Display feature – stack up to eight CS19216 units and display video from up to 8 monitors (dual display / triple display / quad display / multi-display)
- ✓ Video DynaSync™ – an exclusive ATEN technology that eliminates boot-up display problems and optimizes the resolution when switching among different sources



Aprašymas

The ATEN CS19216 16-Port USB 3.0 4K DisplayPort KVM Switch can effectively access and control up to 16 DisplayPort computers from a single USB keyboard, USB mouse, and monitor console. With its dual interface console, users can choose between DisplayPort/HDMI video output supporting high video quality up to 4K DCI (4096 x 2160 @ 60Hz), presenting crystal-clear visuals.

1x CS19216 16-Port USB 3.0 4K DisplayPort KVM Switch with Rack Mounting Kit

2x LIN5-20K1-K13G DisplayPort 1.4 Cables

2x LIN6-11C1-E12G USB 3.0 Cables

2x LIN5-0205-21CG Audio Cables

1x LIN5-04A2-J11G Firmware Upgrade Cable

1x 0X02-0017-000G Foot Pad Set (4 pcs)

1x LIN2-418K-E12G + 0AD8-8012-50M2 Power Adapter

1x User Instructions

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Ports & interfaces	
Number of computers controlled	16
Keyboard port type	USB
Mouse port type	USB
Video port type	DisplayPort
Console ports	3.5mm headphone, 3.5mm mic, DisplayPort, HDMI, USB A
DisplayPorts quantity	16
DisplayPort version	1.2
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	16
Console USB ports quantity	2
USB hub	Yes
USB 3.2 Gen 1 (3.1 Gen 1) Type-A hub ports quantity	2
USB connector type	USB Type-A, USB Type-B
Audio connections	Yes
Headphone outputs	17
Number of microphone inputs	17
DC-in jack	Yes
Performance	
HD type	4K Ultra HD
Maximum resolution	4096 x 2160 pixels
Video bandwidth	60 Hz
Scan interval	1,5,255 s
HDCP	Yes
Firmware upgradeable	Yes
Design	
Product colour	Black
Housing material	Metal
LED indicators	Yes
Push button	Yes

Display

Built-in display	No
------------------	----

Power

Power source	DC
Input voltage	12 V
Power consumption (typical)	26.66 W

System requirements

Windows operating systems supported	Yes
Linux operating systems supported	Yes
Mac operating systems supported	Yes

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Storage relative humidity (H-H)	0 - 80%

Weight & dimensions

Width	432.4 mm
Depth	214.3 mm
Height	44 mm
Weight	4.18 kg

Packaging data

Package width	133 mm
Package depth	499 mm
Package height	324 mm
Package weight	5.33 kg

Packaging content

Quick installation guide	Yes
Manual	Yes

Logistics data

Master (outer) case net weight	12.5 kg
Harmonized System (HS) code	85176200
Master (outer) case width	427 mm
Master (outer) case length	519 mm
Master (outer) case height	348 mm

Master (outer) case gross weight	15.3 kg
Products per master (outer) case	3 pc(s)