

ATEN 2-Port USB 3.1 Gen 1 4K DisplayPort 1.2 KVMP™ Switch with Audio (KVM cables included)

Gamintojas: **ATEN** · Modelis: **CS1922-AT-G** · EAN: **4719264644764** · Prekės kodas: **650540**



197,90 €

Kaina su PVM

Be PVM: **163,55 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports superior video quality – 4K UHD (3840 x 2160 @ 60 Hz) and 4K DCI (4096 x 2160 @ 60 Hz); 2-port USB 3.1 Gen 1 hub with SuperSpeed 5 Gbps data transfer rates
- ✓ Computer selection via front panel pushbuttons, hotkeys and mouse1
- ✓ Multi-Stream Transport (MST) allows multiple monitors through a single DisplayPort connector3
- ✓ DisplayPort Dual-Mode technology (DP++) supports HDMI and DVI signals via a DisplayPort-to-HDMI/DVI DP++ adapter4



Aprašymas

The ATEN CS1922 2-Port USB 3.0 4K DisplayPort KVMP™ Switch provides the latest innovations in desktop KVM switching technology for the increasing demand of higher video quality and transfer speeds on modern computers. The ATEN CS1922 offers an unprecedented performance of delivering 4K resolution, the next generation USB 3.1 Gen 1 hub with SuperSpeed 5 Gbps data transfer rates and enhanced user-friendly operations.

1x CS1922 2-Port USB 3.0 4K DisplayPort KVMP™ Switch

2x LIN5-20K1-K13G DisplayPort Cables

2x LIN6-11C1-E12G USB 3.0 Cables

2x LIN5-0205-21CG Audio Cable

2x LIN5-0205-21DG Audio Cable

1x OAD8-8005-40MG Power Adapter

1x LIN2-418K-E12G Power Cord
1x User Instructions

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Ports & interfaces	
Number of computers controlled	4
Keyboard port type	USB
Mouse port type	USB
Video port type	DisplayPort
Console ports	3.5mm mic, DisplayPort, USB B
DisplayPorts quantity	3
Console USB ports quantity	2
USB hub	Yes
USB 3.2 Gen 1 (3.1 Gen 1) Type-A hub ports quantity	2
USB connector type	USB Type-B
USB version	3.2 Gen 1 (3.1 Gen 1)
Audio connections	Yes
Headphone outputs	4
Number of microphone inputs	4
DC-in jack	Yes
Performance	
HD type	4K Ultra HD
Maximum resolution	4096 x 2160 pixels
Scan interval	1,99 s
HDCP	Yes
Hot-Plug support	Yes
Design	
Product colour	Black
Housing material	Metal, Plastic
LED indicators	Operation, USB
Push button	Yes
Display	
Built-in display	No

Power

Power source	DC
Output voltage	5 V
Power consumption (typical)	2 W
External power adapter	Yes

System requirements

Windows operating systems supported	Yes
Linux operating systems supported	Yes
Mac operating systems supported	Yes

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%

Weight & dimensions

Width	88 mm
Depth	210 mm
Height	55.5 mm
Weight	1.42 kg

Packaging data

Package width	100 mm
Package depth	283 mm
Package height	173 mm
Package weight	1.86 kg

Packaging content

Cables included	Audio (3.5mm), DisplayPort, USB
Manual	Yes
AC adapter included	Yes

Logistics data

Master (outer) case net weight	7.1 kg
Harmonized System (HS) code	85176200
Master (outer) case width	292 mm
Master (outer) case length	517 mm
Master (outer) case height	194 mm
Master (outer) case gross weight	9.8 kg

Products per master (outer) case

5 pc(s)