

## ATEN 2-Port USB 3.0 4K DisplayPort MST KVMP Switch

Gamintojas: **ATEN** · Modelis: **CS1922M-AT-G** · EAN: **4719264645822** · Prekės kodas: **650541**



### 281,91 €

Kaina su PVM

Be PVM: **232,98 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

### Pagrindinės savybės

- ✓ Built-in Multi-Stream Transport (MST) hub allows dual displays (DisplayPort / HDMI) from a single DisplayPort source1
- ✓ Supports superior video quality – 4K UHD (3840 x 2160 @ 60 Hz) and 4K DCI (4096 x 2160 @ 60 Hz); 2-port USB 3.1 Gen 1 hub with SuperSpeed 5 Gbps data transfer speeds
- ✓ Computer selection via front panel pushbuttons, hotkeys, USB mouse, and RS-232 commands4
- ✓ DisplayPort Dual-Mode (DP++) technology supports HDMI and DVI signals via a DisplayPort-to-HDMI/DVI DP++ adapter2



### Aprašymas

Incorporating the latest Multi-Stream Transport (MST) technology, the CS1922M 2-Port USB 3.0 4K DisplayPort MST KVMP™ Switch is the world's first DisplayPort KVM switch with a built-in MST hub. The CS1922M enables users to adopt two console displays from a single DisplayPort 1.2 video source, providing an extended desktop mode and splitter mode at resolutions up to 4K for multitasking across two displays while reducing bulky cable connections.

- 1x 2-Port USB 3.0 4K DisplayPort MST KVMP™ Switch
- 2x LIN5-20K1-K13G DisplayPort 1.2 Cables (1.5m/5ft)
- 2x LIN6-11C1-E12G USB Cables (USB 3.0-A to USB 3.0-B; 1.8m/6ft)
- 4x LIN5-0205-21DG/CD Audio Cables (1.8m/6ft)
- 1x LIN2-418K-E12G / OAD8-8005-40MG Power Adapter
- 1x User Instructions

## Techninė specifikacija

| Specifications                                      |                                                      |
|-----------------------------------------------------|------------------------------------------------------|
| Sandėlio grupė                                      | Server, Storage & Netzwerk > Switche [+1398][-565]   |
| Ports & interfaces                                  |                                                      |
| Number of computers controlled                      | 2                                                    |
| Keyboard port type                                  | USB                                                  |
| Mouse port type                                     | USB                                                  |
| Video port type                                     | DisplayPort                                          |
| Console ports                                       | 3.5mm headphone, 3.5mm mic, DisplayPort, HDMI, USB A |
| DisplayPorts quantity                               | 2                                                    |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity     | 2                                                    |
| Console USB ports quantity                          | 2                                                    |
| USB hub                                             | Yes                                                  |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A hub ports quantity | 2                                                    |
| USB connector type                                  | USB Type-A, USB Type-B                               |
| Audio connections                                   | Yes                                                  |
| Headphone outputs                                   | 4                                                    |
| Number of microphone inputs                         | 4                                                    |
| DC-in jack                                          | Yes                                                  |
| Performance                                         |                                                      |
| HD type                                             | 4K Ultra HD                                          |
| Maximum resolution                                  | 4096 x 2160 pixels                                   |
| Video bandwidth                                     | 60 Hz                                                |
| Scan interval                                       | 1,5,99 s                                             |
| Firmware upgradeable                                | Yes                                                  |
| Design                                              |                                                      |
| Product colour                                      | Black                                                |
| Housing material                                    | Metal, Plastic                                       |
| LED indicators                                      | Yes                                                  |
| Push button                                         | Yes                                                  |
| Hot keys                                            | Yes                                                  |
| Display                                             |                                                      |
| Built-in display                                    | No                                                   |
| Power                                               |                                                      |

|                                   |             |
|-----------------------------------|-------------|
| Power source                      | DC          |
| Input voltage                     | 5 V         |
| Power consumption (typical)       | 4.09 W      |
| Operational conditions            |             |
| Operating temperature (T-T)       | 0 - 50 °C   |
| Storage temperature (T-T)         | -20 - 60 °C |
| Operating relative humidity (H-H) | 0 - 80%     |
| Storage relative humidity (H-H)   | 0 - 80%     |
| Weight & dimensions               |             |
| Width                             | 210 mm      |
| Depth                             | 88 mm       |
| Height                            | 55.5 mm     |
| Weight                            | 560 g       |
| Packaging data                    |             |
| Package width                     | 100 mm      |
| Package depth                     | 283 mm      |
| Package height                    | 173 mm      |
| Package weight                    | 1.84 kg     |
| Packaging content                 |             |
| Quick installation guide          | Yes         |
| Manual                            | Yes         |
| Logistics data                    |             |
| Master (outer) case net weight    | 2.8 kg      |
| Harmonized System (HS) code       | 85176200    |
| Master (outer) case width         | 292 mm      |
| Master (outer) case length        | 517 mm      |
| Master (outer) case height        | 194 mm      |
| Master (outer) case gross weight  | 9.85 kg     |
| Products per master (outer) case  | 5 pc(s)     |