

ATEN 4P USB3.0 DisplayPORT Dual View KVMP SW

Gamintojas: **ATEN** · Modelis: **CS1944DP-AT-G** · EAN: **4719264645969** · Prekės kodas: **650542**



644,91 €

Kaina su PVM

Be PVM: **532,98 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Superior video quality – 4096 x 2160 @ 60Hz and 3840 x 2160 @ 60Hz; 2-Port USB 3.1 Gen 1 hub with SuperSpeed 5 Gbps data transfer rates
- ✓ Quad-Display – Easily connect two CS1944DP units for a second dual-screen setup controlled through a single connection
- ✓ Multi-Stream Transport (MST) allows multiple monitors through a single DisplayPort connector
- ✓ DisplayPort Dual – Mode technology (DP++) supports HDMI and DVI signals via a DisplayPort-to-HDMI/DVI DP++ adapter



Aprašymas

The ATEN CS1944DP desktop KVM switch helps organize your desktop. Especially when managing a multimedia workstation at a large organization, CS1944DP provides you with instant access to two or four computers, all through a single USB keyboard, USB mouse and two DisplayPort monitors.

1x 4-Port USB 3.0 4K DisplayPort Dual Display KVMP™ Switch

8x LIN5-20K1-K13G DisplayPort 1.2 Cables

4x LIN6-11C1-E12G USB 3.0 Cables

8x LIN5-0205-21CG/LIN5-0205-21DG Audio Cables

1x LIN2-418K-E12G Power Adapter

1x User Instructions

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Ports & interfaces	
Number of computers controlled	4
Keyboard port type	USB
Mouse port type	USB
Video port type	DisplayPort
Console ports	3.5mm headphone, 3.5mm mic, DisplayPort, USB A
DisplayPorts quantity	10
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	4
Console USB ports quantity	2
USB hub	Yes
USB 3.2 Gen 1 (3.1 Gen 1) Type-A hub ports quantity	2
Audio connections	Yes
Headphone outputs	6
Number of microphone inputs	6
DC-in jack	Yes
Network	
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1
Performance	
HD type	4K Ultra HD
Maximum resolution	4096 x 2160 pixels
Video bandwidth	60 Hz
Scan interval	1,99 s
Firmware upgradeable	Yes
Design	
Product colour	Black
Housing material	Metal
LED indicators	Yes
Push button	Yes
Hot keys	Yes
Display	

Built-in display	No
Power	
Power source	DC
Input voltage	12 V
Power consumption (typical)	6.125 W
Sustainability	
Compliance certificates	RoHS
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	156.6 mm
Depth	335 mm
Height	44 mm
Weight	3.46 kg
Packaging data	
Package width	116 mm
Package depth	540 mm
Package height	233 mm
Package weight	4.21 kg
Packaging content	
Cables included	Audio (3.5mm), DisplayPort, USB
Manual	Yes
AC adapter included	Yes
Logistics data	
Master (outer) case net weight	10.4 kg
Harmonized System (HS) code	85176200
Master (outer) case width	375 mm
Master (outer) case length	565 mm
Master (outer) case height	258 mm
Master (outer) case gross weight	13.2 kg
Products per master (outer) case	3 pc(s)