

Zebra CS60-HC Handheld bar code reader 1D/2D LED White

Gamintojas: **ZEBRA** · Modelis: **CS6080-HC4F00BVZWW** · EAN: **8596375236530** · Prekės kodas: **650548**



562,90 €

Kaina su PVM

Be PVM: **465,21 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Handheld bar code reader White
- ✓ Scanner type: 1D/2D Sensor type: LED
- ✓ Codabar, Code 11, Code 128, Code 39, Code 93, GS1 DataBar, MSI, Plessey, U.P.C. Aztec Code, Composite Codes, Data Matrix, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39
- ✓ 1280 x 960 pixels
- ✓ Tilt reading angle: -60 - 60°
- ✓ Wireless Standard interfaces: Bluetooth, USB
- ✓ Bluetooth Low Energy (BLE)
- ✓ Power source type: AC, Battery, DC, USB Lithium Polymer (LiPo) 735 mAh



Aprašymas

ULTRA-VERSATILE WITH A FIRST-OF-ITS-KIND CONVERTIBLE DESIGN

The ultra-versatile CS60-HC Healthcare Series Companion Scanner is designed specifically for healthcare and adapts to any clinician workflow. Its groundbreaking design easily converts between corded and cordless operation, handheld and hands-free, as your needs change for superior investment protection. And it features a purpose-built housing that helps offer maximum protection against the spread of bacteria, including a crevice-free surface that helps eliminate places where germs can hide.

ADAPTS TO ANY CLINICIAN WORKFLOW

As a cordless companion scanner, the CS60-HC is small enough to meet any nurse-carry workflow. And as a corded scanner, the CS60-HC provides compact scanning for the pharmacy counter, lab station and more. Whether you purchase a corded or cordless model up front, you can change

modes at any time.

CUTTING-EDGE CLINICAL MOBILITY

With Qi inductive charging, split-second NFC tap-to-pair, Bluetooth 5.0 with Wi-Fi friendly mode, an 18-hour battery and Virtual Tether anti-loss functionality, the cordless CS60-HC is pocketable and wearable when clinician mobility is essential.

PURPOSE BUILT FOR HEALTHCARE

Thanks to a safe LED aimer, night mode and an IP65 sealed disinfectant-ready housing with a crevice-free surface that helps eliminate places where germs can hide, the CS60-HC is designed to be used throughout the whole hospital including the NICU, labour and delivery and mother-baby units.

Techninė specifikacija

Specifications	
Sandėlio grupė	Sonstiges > Barcode Scanner [+994][-201]
Scanning	
Type	Handheld bar code reader
Scanner type	1D/2D
Sensor type	LED
Linear (1D) barcodes supported	Codabar, Code 11, Code 128, Code 39, Code 93, GS1 DataBar, MSI, Plessey, U.P.C.
2D (matrix & stacked) barcodes supported	Aztec Code, Composite Codes, Data Matrix, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39
Optical sensor resolution (W x H)	1280 x 960 pixels
Light levels (direct sunlight)	0 - 108000 lx
Wavelength	525 nm
Tilt reading angle	-60 - 60°
Pitch reading angle	-60 - 60°
Yaw reading angle	0 - 360°
Ports & interfaces	
Connectivity technology	Wireless
Standard interfaces	Bluetooth, USB
Wireless range	100 m
Bluetooth version	5
Bluetooth Low Energy (BLE)	Yes
Performance	
Product colour	White
International Protection (IP) code	IP65
LED indicators	Yes
Certification	FIPS 140-2

Power	
Power source type	AC, Battery, DC, USB
Battery technology	Lithium Polymer (LiPo)
Battery type	Built-in battery
Battery capacity	735 mAh
Number of reads per charge	13000
Battery life	18 h
Charging time	6 h
Power consumption	400 mA
Weight & dimensions	
Weight	87 g
Width	46 mm
Depth	109 mm
Height	23 mm
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%
Technical details	
Compliance certificates	RoHS
Logistics data	
Harmonized System (HS) code	84716070