

ATEN 2-Port USB HDMI KVM Switch with Audio

Gamintojas: **ATEN** · Modelis: **CS692-AT** · EAN: **4710423776814** · Prekės kodas: **650551**



95,90 €

Kaina su PVM

Be PVM: **79,26 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Superior video quality - up to 1920 x 1200 and 1080p
- ✓ Computer selection via a remote port selector, hotkeys, and USB mouse
- ✓ Independent switching of the KVM and Audio focus - one computer has the KVM focus and the other the Audio focus
- ✓ Built-in all-in-one cables (2 x 1.2 m) and bus-powered design



Aprašymas

The CS692 2-Port USB HDMI/Audio Cable KVM Switch links two HDMI-enabled PCs or devices to a single USB keyboard, USB mouse, and HD display console. The CS692 Switch takes a giant step forward from prior cable KVM models in the Petite series, by offering full HDMI functionality, USB 2.0 peripheral sharing (via a USB hub attached to the USB mouse port), and a firmware upgrade function that allows you to keep up with latest available versions.

1x CS692 2-Port USB HDMI/Audio Cable KVM Switch with Remote Port Selector

1x User Instructions

2x Hotkey Stickers

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Netzwerk > Switche [+1398][-565]

Ports & interfaces

Number of computers controlled	2
Keyboard port type	USB
Mouse port type	USB
Video port type	HDMI
Console ports	3.5mm headphone, 3.5mm mic, HDMI, USB A
HDMI ports quantity	2
Console USB ports quantity	2
USB 2.0 Type-A hub ports quantity	4
USB connector type	USB Type-A
Audio connections	Yes
Headphone outputs	3
Number of microphone inputs	3

Performance

HD type	WUXGA
Maximum resolution	1920 x 1200 pixels
Video bandwidth	60 Hz
Scan interval	3,5,10,20 s

Design

Rack mounting	No
Product colour	Black
Housing material	Plastic
LED indicators	Yes
Push button	Yes
Hot keys	Yes

Display

Built-in display	No
------------------	----

Power

Power source	DC
Input voltage	5 V
Power consumption (typical)	0.72 W

Operational conditions

Operating temperature (T-T)	0 - 50 °C
-----------------------------	-----------

Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Storage relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	82.4 mm
Depth	66.5 mm
Height	25.2 mm
Weight	409 g
Packaging data	
Package width	70 mm
Package depth	163 mm
Package height	235 mm
Package weight	550 g
Packaging content	
Quick installation guide	Yes
Manual	Yes
Logistics data	
Master (outer) case net weight	4.09 kg
Harmonized System (HS) code	85176200
Master (outer) case width	395 mm
Master (outer) case length	405 mm
Master (outer) case height	182 mm
Master (outer) case gross weight	6.13 kg
Products per master (outer) case	10 pc(s)