

ATEN 2-Port USB 4K DisplayPort 1.2 KVM Switch (KVM cables included)

Gamintojas: **ATEN** · Modelis: **CS782DP-AT** · EAN: **4719264643644** · Prekės kodas: **650553**



145,90 €

Kaina su PVM

Be PVM: **120,58 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Superior video quality – 4K UHD (3840 × 2160 @ 60 Hz) and 4K DCI (4096 × 2160 @ 60 Hz)
- ✓ Computer selection via remote port selector, hotkeys, and USB mouse; bus-powered design
- ✓ Supports MST (Multi-Stream Transport)2, enabling multiple monitors to be used via a single DisplayPort connector
- ✓ Multiplatform support – Windows, Mac, Sun, and Linux



Aprašymas

With the ever-growing demand for higher video quality and the evolution of DisplayPort technology, 4K-enabled computers and displays are now widely adopted in visually-intensive and commercial applications. Offering up to 4K resolution, the ATEN CS782DP is at home amongst these demanding scenarios and technological advancements.

1x CS782DP 2-Port USB DisplayPort KVM Switch
2x LIN5-20K1-K12G DisplayPort Cables
2x LIN6-04U1-V1BG USB Cables
2x LIN5-0205-21CG Audio Cables
1x Remote Port Selector
1x User Instructions

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Ports & interfaces	
Number of computers controlled	2
Keyboard port type	USB
Mouse port type	USB
Video port type	DisplayPort
Console ports	3.5mm headphone, DisplayPort, USB A
DisplayPorts quantity	2
USB 2.0 Type-B ports quantity	2
USB connector type	USB Type-A, USB Type-B
Audio connections	Yes
Headphone outputs	1
Number of microphone inputs	1
Performance	
HD type	4K Ultra HD
Maximum resolution	4096 x 2160 pixels
Video bandwidth	60 Hz
Scan interval	3,5,10,20 s
Design	
Rack mounting	No
Product colour	Black
Housing material	Plastic
LED indicators	Yes
Hot keys	Yes
Display	
Built-in display	No
Power	
Power source	DC
Input voltage	5 V
Power consumption (typical)	2.18 W
Operational conditions	
Operating temperature (T-T)	0 - 50 °C

Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Storage relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	93 mm
Depth	93.7 mm
Height	26.8 mm
Weight	543 g
Packaging data	
Package width	59 mm
Package depth	239 mm
Package height	175 mm
Package weight	687 g
Packaging content	
Quick installation guide	Yes
Manual	Yes
Logistics data	
Master (outer) case net weight	5.43 kg
Harmonized System (HS) code	85176200
Master (outer) case width	328 mm
Master (outer) case length	497 mm
Master (outer) case height	196 mm
Master (outer) case gross weight	7.71 kg
Products per master (outer) case	10 pc(s)