D-Link AX1800 1800 Mbit/ai Balta Maitinimas per Eternetą (PoE)

Gamintojas: **D-LINK** · Modelis: **DAP-X2810** · EAN: **790069456923** · Prekės kodas: **650760**

155,90 €

Kaina su PVM

Be PVM: **128,84 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 2,4 GHz 575 Mbit/ai
- ✓ 5 GHz 1200 Mbit/ai
- ✓ Didžiausias duomenų perdavimo greitis: 1800 Mbit/ai
- ✓ IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3ab, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u
- ✓ 64-bit WEP, 128-bit WEP, SSID, SSL/TLS, WPA, WPA2, WPA3
- ✓ Maitinimas per Eternetą (PoE)
- ✓ Antenų kiekis: 2 Vidinis



Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903



Aprašymas

Simple-to-manage and easy-to-scale Wi-Fi 6 for your business.
The Wi-Fi 6-ready DAP-X2810 provides businesses of all sizes with incredible speeds, significantly increased capacity and interference-free coverage, combined with centralised management by Nuclias Connect.

Manage your business network with ease

The DAP-X2810 works with our Nuclias Connect software-based management platform (with optional hardware controller) that enables you to manage and control your business network from anywhere with an internet connection, for easy access, automation, and network scalability.

Easily manage your network with Nuclias Connect

Automate, monitor, manage and scale your network in line with business demand without the complexity or cost, through the centrally managed Nuclias Connect platform.

Next-gen Wi-Fi 6

Delivers greater network efficiency and lower latency, with nearly x4 the capacity of previous Wi-Fi standards

Intelligent, secure performance

Superior security with WPA3™ wireless encryption, and high throughput with dual-band, 2x2 MU-MIMO technology, band steering & airtime fairness that intelligently manages users.

Flexible installation with PoE

Supports Power over Ethernet (802.3at) for a simpler installation with less cable clutter & includes a wall-plate design for installation on Ethernet wall sockets.

License-Free Access Point

Works as a standalone AP or as part of a centralised, scalable multi-device deployment in line with business demand.

Minimise the hassle of admin tasks

Empower admins to work efficiently & effectively with role-based options that enable delegated access across your network. You can deploy, configure, update and expand rapidly.

Branded Captive Portal

A branded Captive Portal with industry-standard authentication for enhanced access management.

Free-to-download software & app

Rapidly setup, manage and monitor APs locally via our free network management software, or remotely with the Nuclias Connect app

Next-gen Wi-Fi 6 performance that turbo boosts your business

With combined Wi-Fi 6 802.11ax speeds of up to 1,800 Mbps, the DAP-X2810 provides lightning-fast connectivity, enabling large data transfer and superior quality video streaming, even in highly congested environments.

As the next-generation of connectivity, Wi-Fi 6 delivers greater network efficiency and lower latency, with nearly four times the capacity of previous Wi-Fi standards.

Optimised Wi-Fi for a superior client experience.
The DAP-X2810 supports Band steering, 2x2 MU-MIMO and beamforming - all designed to work together to alleviate congestion.

And Load Balancing and Airtime Fairness technology distributes workloads between APs for optimum resource utilisation - allowing every device in your network to seamlessly get the best connectivity possible, without putting a strain on your whole network.

Multiple Operation Modes

The DAP-X2810 can be configured to fit the needs of your network and optimise performance.

- Access point
- Wireless distribution system
(WDS) with access point
- WDS/bridge (no AP broadcasting)
- Wireless client.

Simple and clean installation, anywhere.
It can be ceiling-mounted, wall-mounted, or placed on a desk. The DAP-X2810’s PoE function allows for an easy installation. No need to run extra power lines and no more cable clutter. Perfect for advanced installations in areas where power outlets are not readily available.

Manage your business network with powerful controls

Nuclias Connect enables you to manage and control your network from anywhere and provides an extensive understanding of your network and its users through traffic analytics and status reports via a web browser or our free app. Insights derived from this traffic data can be used to create business value, and traffic can be viewed across the entire network and all the way down to the level of a single Access Point.

Comprehensive on-site network management

Compared to traditional hardware-based unified management systems, Nuclias Connect offers tremendous flexibility. Easy setups, remote access, and an intuitive dashboard make life easier for network admins, whilst functionality and network self-healing tools such as airtime fairness, localised throttling and load-balancing improves overall user experience.

Scale your Wi-Fi alongside your business, from anywhere

Nuclias Connect is designed with unlimited scalability, allowing you to tailor to the demands of the business. Adding a new site or expanding an existing one is quick and easy as all management and configuration is done through the cloud, with access points and surveillance cameras being ready to deploy straight out of the box and be automatically discovered by the software.

Get your guests online through a captive portal

Not only can your guests connect using just their email address, Facebook or Google account, our Captive Portal also gives your business the opportunity to increase brand awareness, advertise promotions and collate user insights that enable businesses to better understand their customers.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Nuclias hardware controller

The DNH-100 Wireless Controller provides an inexpensive, ready-made solution, and removes the need for installing and maintaining Nuclias Connect on additional hardware such as a server or PC. It supports up to 100 APs, automatically detects devices, pushes configurations, and provides robust hardware management. Simply plug in and power on.

Techninė specifikacija

Savybės	
2,4 GHz	Taip
5 GHz	Taip
Didžiausias duomenų perdavimo greitis	1800 Mbit/ai
Maksimalus duomenų perdavimo greitis (2,4 GHz)	575 Mbit/ai
Maksimalus duomenų perdavimo greitis (5 GHz)	1200 Mbit/ai
Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
Dažnių juosta	2.4/5 GHz
Tinklo standartai	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3ab, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u
MIMO	Taip
MIMO tipas	Multi User MIMO
„Wi-Fi“ multimedijos (WMM) / (WME)	Taip
Naudotojų nukreipimas	Taip
„Airtime Fairness“ (ATF)	Taip
Vidutinis laikas tarp trikčių (MTBF)	30000 h
Saugumas	
Apsaugos algoritmų palaikymas	64-bit WEP, 128-bit WEP, SSID, SSL/TLS, WPA, WPA2, WPA3
Valdymo funkcijos	
Web pagrįstas valdymas	Taip
Ryšys	
Ethernet LAN (RJ-45) portų kiekis	2
DC įėjimo lizdas	Taip
Energijos valdymas	
Maitinimas per Eternetą (PoE)	Taip
AC įėjimo įtampa	12 V
Įvesties srovė	2.5 A
Galios suvartojimas (maks.)	19,44 W
Konstrukcija	

Produkto spalva	Balta
Atstatymo mygtukas	Taip
LED indikatoriai	Energija, Būsena
Antena	
Antenos tipas	Vidinis
Antenų kiekis	2
Antenos stiprinimo lygis (max)	4,3 dBi
Sertifikatai	
Atitikties sertifikatai	CE
Sertifikavimas	FCC
Svoris ir matmenys	
Plotis	170 mm
Ilgis	170 mm
Aukštis	28 mm
Svoris	477,4 g
Aplinkos sąlygos	
Darbo santykinės drėgmės diapazonas	10 - 90%
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-20 - 65 °C
Sandėliavimo santykinis drėgmės diapazonas	5 - 95%
Logistikos duomenys	
Darniosios sistemos (DS) kodas	85176990
Tvarumas	
Tvarumo reikalavimų laikymasis	Taip
Matmenys ir svoris	
Matmenys (I × P × A)	25,00cm × 25,00cm × 9,00cm

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Greitos pradžios vadovas
- Gaminio lankstinukas
- Atitikties deklaracija
- Vaizdo įrašas youtube.com/watch?v=P30pMbSnsec

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Gamintojo ir saugos informacija

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux
Postbus 48, 5480 AA Schijndel, NL
dlink.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- Atitikties deklaracija