

TP-Link AX1500 Whole Home Mesh Wi-Fi 6 System

Gamintojas: **TP-LINK** · Modelis: **DECO X1500(2-PACK)** · EAN: **4895252505108** · Prekės kodas: **650845**



142,90 €

Kaina su PVM

Be PVM: **118,10 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Mesh system White
- ✓ Antenna type: Internal
- ✓ Dual-band (2.4 GHz / 5 GHz) Wi-Fi 6 (802.11ax) 1500 Mbit/s
- ✓ WPA-Personal, WPA2-Personal, WPA3
- ✓ Point-to-point protocol over Ethernet (PPPoE) Dynamic IP Static IP Wireless Distribution System (WDS) bridge
- ✓ Quality of Service (QoS) support Port forwarding



Techninė specifikacija

Specifications	
Sandėlio grupė	Server/Storage/Network > Access Points/Routers [+1151][-307]
Design	
Product colour	White
Antenna type	Internal
Product type	Mesh system
LED indicators	Power

Reset button	Yes
Wireless LAN features	
Wi-Fi band	Dual-band (2.4 GHz / 5 GHz)
Top Wi-Fi standard	Wi-Fi 6 (802.11ax)
WLAN data transfer rate (max)	1500 Mbit/s
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)
WLAN data transfer rate (first band)	300 Mbit/s
WLAN data transfer rate (second band)	1201 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Security algorithms	WPA-Personal, WPA2-Personal, WPA3
Number of guest networks (5 GHz)	1
Number of guest networks (2.4 GHz)	1
Point-to-point protocol over Ethernet (PPPoE)	Yes
Dynamic IP	Yes
Static IP	Yes
Wireless Distribution System (WDS) bridge	Yes
IGMP proxy	Yes
IGMP snooping	Yes
Tagged VLAN	Yes
Dynamic DNS (DDNS)	Yes
Guest access	Yes
Apps supported	TP-Link Deco
Features	
Quality of Service (QoS) support	Yes
Port forwarding	Yes
BeamForming	Yes
Parental control	Yes
Parental control features	Bedtime, Custom profiles, Family time, Off time, Professional content filter library, Time rewards
MU-MIMO technology	Yes
MIMO	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
DC-in jack	Yes
Certificates	

Certification	CE, FCC, RoHS, JPA, JRF, VCCI, NCC, BSMI
---------------	--

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	110 mm
Depth	110 mm
Height	114 mm

Packaging content

AC adapter included	Yes
Number of units included	2 pc(s)
Ethernet cable	Yes
Quick installation guide	Yes