D-Link DGS-1210-10MP Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black, Grey

Gamintojas: **D-LINK** · Modelis: **DGS-1210-10MP/E** · EAN: **790069467714** · Prekės kodas: **650915**



221.90€

Kaina su PVM

Be PVM: **183.39€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Free centralised management with Nuclias Connect
- ✓ Layer 2 management and security with Layer 3 capabilities
- ✓ Compact Command-Line Interface (CLI) and web-based User-Interface
- ✓ Static Routing and MSTP
- ✓ PoE options up to 370W power budget
- ✓ Dual image & config





Aprašymas

Static Routing

Route Layer 3 traffic between switches, even if they're segmented in VLANs.

Fibre Uplink Ports

Connect to other areas of your network at fibre-optic Gigabit speeds, and reach even further distances.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Surveillance Mode Interface

D-Link’s exclusive, easy-to-use Surveillance Mode interface gives you a snapshot of your security topology in an instant.

PoE Capable
Up to 370 W PoE output per switch

VLANs

Segment your network into VLANs.

Dual Image

Risk-free configuration testing.

Smart Managed with a Plus
With increased PoE output, advanced Layer 2 management features, and Layer 3 static routing , D-Link’s DGS-1210 Smart+ Managed Gigabit Switches provide a cost-efficient and flexible solution for expanding any business network.

Advanced Layer 2 Management with Layer 3 Static Routing

The DGS-1210 Smart+ family has advanced network management options, accessible via Compact CLI or the Web-based UI, that equip your business with network capabilities such as VLANs, multiple spanning tree protocol (MSTP), link aggregation (LACP), static routing, dual software images, and dual configuration files.

With powerful security features like IGMP snooping, access control lists, port security, and the unique D-Link Safeguard Engine that protects your network against malicious denial-of-service attacks from broadcast, multicast and unicast flooding, the DGS-1210 Smart+ family is a versatile solution for access-edge network environments.

Fibre Uplinks

Use fibre uplinks to connect across longer distances, like factory lines and university campuses, using lightweight, secure, and energy-efficient fibre optic cabling that’s immune to interference and which has access to higher throughput to protect the future demands of your business network.

PoE and PoE+, with budgets up to 370W

The DGS-1210 Smart+ Series includes a range of high power budget PoE-enabled switches for businesses looking to power larger deployments of VoIP phones, wireless access points or network cameras.

This product is compatible with Nuclias Connect

Nuclias Connect is our free remote network management software designed with network scalability, privacy and customisation in mind. It can be used either as an on-premises software management platform, or as a cloud solution.

Free Network Design and Management Software

D-Link’s free Network Assistant (DNA) displays all connected devices and speeds up the first time configuration. The free D-View 7 Network Management System comes with a license for 25 nodes and 2 probes and full access to the management tools. Optional upgrade licenses allow you to broaden your network and analysis.

Smart Energy-Saving Design

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

D-Link Green technology enables the DGS-1210 Smart+ series to save power without any sacrifices. The majority of the family utilises a fanless design, otherwise they feature a smart fan that powers on above a certain temperature. All come with advanced silicon technology which saves up to 73% of energy compared to a normal switch.

Surveillance Mode

Select Surveillance Mode in the Web UI to take advantage of easy-to-use surveillance features which enable you to manage your surveillance network effortlessly. It automatically detects your security devices and segments them into a dedicated Auto Surveillance VLAN to handle video surveillance traffic securely and efficiently.

Free Next-Business-Day Service

Enjoy our free Next Business Day service, as standard, to replace faulty equipment quickly.

Our rapid-response technical support is designed to ensure businesses get the best support for their unique environment. Our extended warranty and enhanced service packages increase the lengths of warranties and further minimises downtime. You can even opt for our Same Business Day Service which guarantees the delivery of the replacement product within 4 hours of confirmation of product failure.

Techninė specifikacija

Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	2
Installed SFP+ modules quantity	0
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Port mirroring	Yes
Full duplex	Yes
Half duplex	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Auto MDI/MDI-X	Yes
Spanning tree protocol	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Head-of-line (HOL) blocking	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
VLAN support	Yes
Number of VLANs	256
Data transmission	
MAC address table	8000 entries
Switching capacity	20 Gbit/s
Forwarding rate	14.88 Mpps
Static route	Yes
Number of static routes	256
Jumbo frames support	Yes
Jumbo frames	10000
Packet buffer memory	4.1 MB
Security	
IGMP snooping	Yes
Loop protection	Yes
Design	
Product colour	Black, Grey
LED indicators	Yes
Performance	
Internal memory	128 MB
Flash memory	32 MB
Mean time between failures (MTBF)	1274005 h
Power	
Power source	AC
Power supply included	Yes
Number of power supply units	1
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	9.4 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	8
Total Power over Ethernet (PoE) budget	130 W

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Operational conditions	
Operating temperature (T-T)	-5 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Heat dissipation	507.23 BTU/h
Weight & dimensions	
Width	330 mm
Depth	180 mm
Height	44 mm
Weight	1.77 kg
Certificates	
Compliance certificates	BSMI, CB, CCC, cUL
Sustainability	
Sustainability compliance	Yes

Gamintojo ir saugos informacija

MANUFACTURER

D-Link

EU RESPONSIBLE PERSON

D-Link Benelux
Postbus 48, 5480 AA Schijndel, NL
dlink.com

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt