

D-Link Hi-speed USB 2.0 10/100 Ethernet Adapter

Gamintojas: **D-LINK** · Modelis: **DUB-E100** · EAN: **7900692459540** · Prekės kodas: **651396**



27,90 €

Kaina su PVM

Be PVM: **23,06 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ USB Ethernet
- ✓ 100 Mbit/s 10/100BaseT(X)
- ✓ Component for: PC

Aprašymas

The D-Link DUB-E100 is a Hi-Speed USB 2.0 10/100Mbps Fast Ethernet Adapter specifically designed to plug into an available Universal Serial Bus (USB) port on a desktop or laptop PC running Microsoft Windows XP, Me, 2000 or 98SE. Based on USB 2.0, the DUB-E100 extends the transfer speed of earlier USB Fast Ethernet adapters to true 10/100Mbps connectivity.

As a USB device, the D-Link DUB-E100 eliminates the need to use an ISA, PCI, or PC Card slot to add LAN connectivity to a PC desktop or laptop computer. Installation and use are further simplified by living up to USB's out-of-the-box installation approach to connecting computer peripherals. You will not need to open the case of your computer, nor will you be required to set IRQ's. The D-Link DUB-E100 represents the simplest way to connect your computer to an Ethernet based network.

The D-Link DUB-E100 provides a standard RJ-45 connector for a quick and simple method of connecting to an Ethernet 10Mbps or Fast Ethernet 100Mbps based LAN via a network hub or switch. The built-in USB 2.0 cable connects directly to your computer or laptop.

Power for the DUB-E100 is provided directly by the USB bus, eliminating the need for an external power adapter. It also supports USB's energy saving suspend and resume functions to minimize power consumption, which is especially useful for laptop/notebook users.

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Network > Network Adapters [+1948][-605]

Ports & interfaces

Connectivity technology	Wired
Host interface	USB
Interface	Ethernet
Ethernet LAN (RJ-45) ports	1

Network

Maximum data transfer rate	100 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3u
Cabling technology	10/100BaseT(X)
Full duplex	Yes

Design

Internal	No
Component for	PC
Product colour	Black
LED indicators	Link, Power
Certification	FCC Class B, CE Class B

Power

Input current	0.5 A
Power consumption (typical)	2.5 W
Power consumption	150 mA

System requirements

Windows operating systems supported	Yes
Mac operating systems supported	Yes
Linux operating systems supported	Yes

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	0 - 95%

Weight & dimensions

Width	21.3 mm
Depth	73 mm
Height	20 mm
Weight	22 g

Packaging data

Package width	138 mm
Package depth	138 mm
Package height	30 mm
Package weight	116 g

Logistics data

Harmonized System (HS) code	85176990
Shipping (inner) case net weight	1.88 kg
Shipping (inner) case length	36 cm
Shipping (inner) case height	34.5 cm
Shipping (inner) case width	32 cm
Products per shipping (inner) case	40 pc(s)
Pallet gross weight (air)	378 kg
Master (outer) cases per pallet (air)	45 pc(s)
Products per pallet (air)	1800 pc(s)
Pallet height (air)	186 cm
Pallet gross weight (sea)	378 kg
Master (outer) cases per pallet (sea)	45 pc(s)
Products per pallet (sea)	1800 pc(s)
Pallet height (sea)	186 cm
Shipping (inner) case gross weight	8.4 kg
Pallet gross width	110 cm
Pallet gross length	120 cm

Other features

Compliance industry standards	OHCI, EHCI
Supported data transfer rates	10/100
Ports quantity	1