

TP-Link Omada EAP610GP-DESKTOP wireless access point 1201 Mbit/s White Power over Ethernet (PoE)

Gamintojas: **TP-LINK** · Modelis: **EAP610GP-DESKTOP** · EAN: **8885020620504** · Prekės kodas: **651530**

145,90 €

Kaina su PVM

Be PVM: **120,58 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Seamless 1.8 Gbps WiFi 6 Speeds: 1201 Mbps on 5 GHz & 574 Mbps on 2.4 GHz
- ✓ 1x GPON Port for High-Speed and Ultra-Range Access
- ✓ Ultra-Broadband WiFi 6: MU-MIMO, Seamless Roaming\$
- ✓ One Fiber for Multiple Services: Wired, Wireless, Voice, VoIP, Data, and HD Video Services
- ✓ VoIP Calls: Support multiple VoIP accounts and various call features, exceeding traditional landlines
- ✓ Easy Use: One-Click Pairing and Automatic Adoption
- ✓ Smart O&M: PPSK△ and Multiple Portals\$
- ✓ High Flexibility: Support both desktop and wall mounting setups
- ✓ Centralized Management: Integrates with the Unified Optical Solution

Techninė specifikacija

Specifications

Sandėlio grupė

Server/Storage/Network > Access Points/Routers [+1151][-307]

Features

2.4 GHz	Yes
5 GHz	Yes
6 GHz	No
Maximum data transfer rate	1201 Mbit/s
Maximum data transfer rate (2.4 GHz)	574 Mbit/s

Maximum data transfer rate (5 GHz)	1201 Mbit/s
Ethernet LAN data rates	1000 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Number of users	120 user(s)
Channel bandwidth	80 MHz
MIMO	Yes
MIMO type	Multi User MIMO
Spread spectrum method	OFDMA
Wi-Fi roaming	Yes
VLAN support	Yes
Rate limiting	Yes
Wireless isolation	Yes
Band steering	Yes
Airtime Fairness (ATF)	Yes
Quality of Service (QoS) support	Yes
BeamForming	Yes
Transmitting power (CE)	20 dBm
Transmitting power (FCC)	25 dBm
Security	
Security algorithms	SNMP, SNMPv2, SNMPv3, SSH, WPA-Personal, WPA2-Personal, WPA3-Personal
MAC address filtering	Yes
Service Set Identifier (SSID) features	Multiple SSIDs, SSID broadcast on/off
Number of SSID supported	16
Remote Authentication Dial-In User Service (RADIUS)	Yes
Management features	
Web-based management	Yes
Syslog	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	4
USB 2.0 ports quantity	0
Power	
Power over Ethernet (PoE)	Yes
DC voltage range	53.5 V
Power consumption (typical)	17.3 W

Design

Placement	Desk, Wall
Product colour	White
Reset button	Yes
LED indicators	Power

Antenna

Antenna type	Internal
Antenna direction type	Omni-directional
Antennas quantity	2
Antenna gain level (max)	5 dBi

Certificates

Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Certification	CE, FCC, RoHS, IC

Weight & dimensions

Width	175 mm
Depth	140 mm
Height	33 mm
Weight	492 g

Packaging content

Quantity per pack	1 pc(s)
Mounting kit	Yes
Quick start guide	Yes

Operational conditions

Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%

Sustainability

Sustainability compliance	Yes
---------------------------	-----