

TP-Link Omada EAP613 WLAN prieigos taškas 1775 Mbit/ai Balta Maitinimas per Eternetą (PoE)

Gamintojas: **TP-LINK** · Modelis: **EAP613** · EAN: **4895252500516** · Prekės kodas: **651532**



132,89 €

Kaina su PVM

Be PVM: **109,83 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 2,4 GHz 574 Mbit/ai
- ✓ 5 GHz 1201 Mbit/ai
- ✓ Didžiausias duomenų perdavimo greitis: 1775 Mbit/ai
- ✓ IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
- ✓ HTTPS, SNMP, SNMPv2, SNMPv3, WPA, WPA2, WPA3
- ✓ Maitinimas per Eternetą (PoE)
- ✓ Antenų kiekis: 4 Vidinis



Aprašymas

Easily Upgrade to Business WiFi 6 Network

AX1800 Ceiling Mount WiFi 6 Access Point

AX1800 WiFi 6 Speed

574 Mbps on 2.4 GHz + 1201 Mbps on 5 GHz†

Seamless Roaming

Uninterrupted streaming when moving between APs§

Ultra-Slim Design

Φ160 mm × 33.6 mm elegant design brings more agility

High-Efficiency WiFi 6

More connected devices can enjoy faster speeds

Omada Mesh Technology

More flexible and convenient wireless deployment

Gigabit Wired Performance

Boosts overall throughput with a Gigabit Ethernet port

Centralized Cloud Management

Manage the whole network locally or from the cloud

PoE+ Powered

Supports DC (adapter is not included), 802.3at PoE+, and Passive PoE for flexible installations

Optimized WiFi Performance

With Portal Authentication, MU-MIMO, Band Steering, Airtime Fairness, and Load Balance

Upgrade to WiFi 6, Power up Your Business

WiFi 6 brings faster speeds, less lag, and higher capacity.

Superior WiFi 6 Speeds

Upgrade to WiFi 6 with speeds up to 1775 Mbps brings 50% faster speeds than WiFi 5.† Every application feels more fluid with drastically improved Wi-Fi speeds

Seamless Integration into Omada SDN

The Omada Software Defined Networking (SDN) platform integrates network devices, including access points, switches, and routers. It provides 100% centralized cloud management and creates a highly scalable network controlled from a single interface.

Auto Channel Selection and Power Adjustment to Optimize Overall Performance

Provides powerful wireless performance while significantly reducing WiFi interference by automatically adjusting the channel settings and transmission power levels of neighboring APs in the same network

Easy Deployment & Higher Performance by Omada Mesh

Easy Pairing, Less Wiring

With Mesh technology, Omada EAPs save you from extra wires by wirelessly extending your WiFi signal further and more flexibly to hard-to-wire areas.

Optimized Network Performance

Intelligent self-organization optimizes the best path between EAPs while self-healing ensures you stay online even when one AP is disrupted.

Always Stay Smooth with Fast Roaming

Ensures customers to enjoy uninterrupted streaming when moving around by switching clients automatically to the access points with the optimal signal.

Ultra-Slim Design Brings More Agility

Exceptional performance with compact design ensures simple WiFi installation while saving space. The elegant appearance makes EAP613 perfectly blend into any modern office, hotel, classroom, or café.

Easy to Mount with Refined Industrial Design

Boosted Network Security and Efficiency

Secure Guest Network with Up to 16 SSIDs

Guest network access provides enhanced security to guests. Different SSIDs also enable flexible access management.

Guest Network with SMS Login

Captive portal (including SMS and Voucher) and 802.1x authentication help maintain authorized guests to use the network. Boost your business with a customized marketing page

WPA3 for Worry-Free Open Public Networks

With advanced enterprise security, WPA3 provides more data security for previously unsecured and open WiFi hotspots.

Band Steering

Automatically moves dual band devices onto the wider 5GHz band for faster connections.

Load Balance

Ensures large numbers of users have smooth network experiences in high-density business networks

Airtime Fairness

Increases average network throughput in heavily congested environments

Techninė specifikacija

Savybės	
2,4 GHz	Taip
5 GHz	Taip
6 GHz	Ne

Didžiausias duomenų perdavimo greitis	1775 Mbit/ai
Maksimalus duomenų perdavimo greitis (2,4 GHz)	574 Mbit/ai
Maksimalus duomenų perdavimo greitis (5 GHz)	1201 Mbit/ai
Eterneto LAN duomenų perdavimo norma	100,1000 Mbit/ai
Dažnių juosta	2.4 - 5 GHz
Tinklo standartai	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Automatinis kanalo pasirinkimas	Taip
Automatinis kanalų nuskaitymas	Taip
MIMO	Taip
MIMO tipas	Multi User MIMO
Plėstinis spektro metodas	OFDMA
„Wi-Fi“ multimedijos (WMM) / (WME)	Taip
VLAN palaikymas	Taip
Reitingo apribotojimas	Taip
Belaidžio ryšio atskyrimas	Taip
Naudotojų nukreipimas	Taip
„Airtime Fairness“ (ATF)	Taip
Spindulio susidarymas	Taip
Perdavimo galia (CE)	<20 dBm(2.4 GHz, EIRP); <23 dBm(5 GHz band1/2, EIRP); <25 dBm (5 GHz band3)
Perdavimo galia (FCC)	<25 dBm (2.4 GHz); <25 dBm (5 GHz)

Saugumas

Apsaugos algoritmų palaikymas	HTTPS, SNMP, SNMPv2, SNMPv3, WPA, WPA2, WPA3
Palaikomų SSID diskų skaičius	16

Valdymo funkcijos

Web pagrįstas valdymas	Taip
Valdymo platforma	Omada

Ryšys

Ethernet LAN (RJ-45) portų kiekis	1
USB 2.0 portų kiekis	0
DC įėjimo lizdas	Taip

Energijos valdymas

Maitinimas per Eternetą (PoE)	Taip
Palaikomas maitinimo per eternetą (en. PoE) tipas	Passive PoE
DC įtampos stiprumo intervalas	12 V

Išvesties srovė	1 A
Energijos suvartojimas	9,6 W
Galios suvartojimas (maks.)	10,6 W
Konstrukcija	
Talpinimo	Lubos, Siena
Produkto spalva	Balta
Atstatymo mygtukas	Taip
LED indikatoriai	Taip
Antena	
Antenos tipas	Vidinis
Antenų kiekis	4
Antenos stiprinimo lygis (max)	5 dBi
Veikimo charakteristikos	
Suderinamos operacinės sistemos	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux
Sertifikatai	
Sertifikavimas	CE, FCC, RoHS
Svoris ir matmenys	
Plotis	160 mm
Ilgis	160 mm
Aukštis	33,6 mm
Pakuotės turinys	
Kiekis pakuotėje	1 vnt
Montavimo rinkinys	Taip
Greitos pradžios vadovas	Taip
Aplinkos sąlygos	
Darbo santykinės drėgmės diapazonas	0 - 40%
Darbo temperatūros diapazonas (TT)	10 - 90 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 70 °C
Sandėliavimo santykinis drėgmės diapazonas	5 - 90%
Matmenys ir svoris	
Matmenys (I × P × A)	23,00cm × 24,00cm × 7,00cm

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Greitos pradžios vadovas](#)
- › [Gaminio lankstinukas](#)
- › [Saugos informacija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbHNiederkasseler Lohweg 175, 40547 Düsseldorf,
DEtp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURUV. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- › [Saugos informacija](#)