

# TP-Link Omada AX3000 Wall Plate WiFi 6 Access Point

Gamintojas: **TP-LINK** · Modelis: **EAP615-WALL(5-PACK)** · EAN: **8885020622898** · Prekės kodas: **651536**



## 447,91 €

Kaina su PVM

Be PVM: **370,17 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Superior WiFi 6 Speeds - Delivers dual-band speeds of up to 18 Gbps powered by the latest WiFi 6 technology
- ✓ Complete In-Room WiFi Coverage - Guarantees strong signals and corner-to-corner WiFi coverage in each room
- ✓ Higher Network Efficiency - OFDMA and DL/UL MU-MIMO\* deliver data to multiple devices simultaneously with less lag
- ✓ Full Gigabit Ports - Connect multiple devices with four gigabit ports and one downlink port offering PoE pass-through
- ✓ Centralized Cloud Management - Integrates into Omada SDN for cloud access and remote management



## Aprašymas

### The Smarter Cloud Solution for Business Networking.

AX1800 Wall Plate WiFi 6 Access Point

Futureproof Your Network with WiFi 6 Connectivity

Connect more devices at the same time with WiFi 6 speeds of up to 1800 Mbps..

Corner-to-Corner Indoor WiFi Coverage

Guests can enjoy strong private networks that paint their entire space by installing EAP615-Walls in each guest room.

## Techninė specifikacija

| Specifications                                      |                                                                                                                                |
|-----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Sandėlio grupė                                      | Server/Storage/Network > Access Points/Routers [+1151][-307]                                                                   |
| Features                                            |                                                                                                                                |
| 2.4 GHz                                             | Yes                                                                                                                            |
| 5 GHz                                               | Yes                                                                                                                            |
| 6 GHz                                               | No                                                                                                                             |
| Maximum data transfer rate                          | 1774 Mbit/s                                                                                                                    |
| Maximum data transfer rate (2.4 GHz)                | 574 Mbit/s                                                                                                                     |
| Maximum data transfer rate (5 GHz)                  | 1201 Mbit/s                                                                                                                    |
| Ethernet LAN data rates                             | 10,100,1000 Mbit/s                                                                                                             |
| Frequency band                                      | 2.4 - 5 GHz                                                                                                                    |
| Networking standards                                | IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3af, IEEE 802.3at  |
| Cabling technology                                  | 10/100/1000Base-T(X)                                                                                                           |
| Automatic channel selection                         | Yes                                                                                                                            |
| Automatic channel scanning                          | Yes                                                                                                                            |
| MIMO                                                | Yes                                                                                                                            |
| MIMO type                                           | Multi User MIMO                                                                                                                |
| VLAN support                                        | Yes                                                                                                                            |
| Rate limiting                                       | Yes                                                                                                                            |
| Wireless isolation                                  | Yes                                                                                                                            |
| Band steering                                       | Yes                                                                                                                            |
| Airtime Fairness (ATF)                              | Yes                                                                                                                            |
| Quality of Service (QoS) support                    | Yes                                                                                                                            |
| BeamForming                                         | Yes                                                                                                                            |
| Transmitting power (CE)                             | 23 dBm                                                                                                                         |
| Transmitting power (FCC)                            | 21 dBm                                                                                                                         |
| Security                                            |                                                                                                                                |
| Security algorithms                                 | HTTPS, SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise, WPA3-Personal |
| MAC address filtering                               | Yes                                                                                                                            |
| Service Set Identifier (SSID) features              | Multiple SSIDs                                                                                                                 |
| Number of SSID supported                            | 16                                                                                                                             |
| Remote Authentication Dial-In User Service (RADIUS) | Yes                                                                                                                            |

|                                |                                                                                  |
|--------------------------------|----------------------------------------------------------------------------------|
| Access Control List (ACL)      | Yes                                                                              |
| <b>Protocols</b>               |                                                                                  |
| STelnet using SSH v2           | Yes                                                                              |
| <b>Management features</b>     |                                                                                  |
| Web-based management           | Yes                                                                              |
| Syslog                         | Yes                                                                              |
| Firmware upgradeable           | Yes                                                                              |
| <b>Ports &amp; interfaces</b>  |                                                                                  |
| Ethernet LAN (RJ-45) ports     | 4                                                                                |
| USB 2.0 ports quantity         | 0                                                                                |
| <b>Power</b>                   |                                                                                  |
| Power over Ethernet (PoE)      | Yes                                                                              |
| Power consumption (typical)    | 10 W                                                                             |
| <b>Design</b>                  |                                                                                  |
| Placement                      | Wall                                                                             |
| Product colour                 | White                                                                            |
| Cable lock slot                | Yes                                                                              |
| On/off switch                  | Yes                                                                              |
| Reset button                   | Yes                                                                              |
| LED indicators                 | Power                                                                            |
| <b>Antenna</b>                 |                                                                                  |
| Antenna type                   | Internal                                                                         |
| Antennas quantity              | 4                                                                                |
| Antenna gain level (max)       | 4 dBi                                                                            |
| <b>Performance</b>             |                                                                                  |
| Compatible operating systems   | Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows 10, Windows 11, Linux |
| <b>Certificates</b>            |                                                                                  |
| Compliance certificates        | CE, Federal Communications Commission (FCC), RoHS                                |
| <b>Weight &amp; dimensions</b> |                                                                                  |
| Width                          | 143 mm                                                                           |
| Depth                          | 86 mm                                                                            |
| Height                         | 20 mm                                                                            |
| <b>Packaging data</b>          |                                                                                  |
| Package width                  | 385 mm                                                                           |

|               |        |
|---------------|--------|
| Package depth | 495 mm |
|---------------|--------|

|                |        |
|----------------|--------|
| Package height | 210 mm |
|----------------|--------|

|                |       |
|----------------|-------|
| Package weight | 330 g |
|----------------|-------|

#### Packaging content

|                   |         |
|-------------------|---------|
| Quantity per pack | 5 pc(s) |
|-------------------|---------|

|              |     |
|--------------|-----|
| Mounting kit | Yes |
|--------------|-----|

|                   |     |
|-------------------|-----|
| Quick start guide | Yes |
|-------------------|-----|

#### Operational conditions

|                                   |          |
|-----------------------------------|----------|
| Operating relative humidity (H-H) | 10 - 90% |
|-----------------------------------|----------|

|                             |           |
|-----------------------------|-----------|
| Operating temperature (T-T) | 0 - 40 °C |
|-----------------------------|-----------|

|                           |             |
|---------------------------|-------------|
| Storage temperature (T-T) | -40 - 70 °C |
|---------------------------|-------------|

|                                 |         |
|---------------------------------|---------|
| Storage relative humidity (H-H) | 5 - 90% |
|---------------------------------|---------|