

LevelOne FEP-0631 network switch Fast Ethernet (10/100) Power over Ethernet (PoE) Black

Gamintojas: **LEVELONE** · Modelis: **FEP-0631** · EAN: **4015867225851** · Prekės kodas: **651876**



47,90 €

Kaina su PVM

Be PVM: **39,59 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ IEEE 802.3af/at PoE compliant to simplify deployment and installation
- ✓ Supports port-based VLAN
- ✓ Connection distance of up to 250m at 10Mbps data rate
- ✓ Auto-detection and protection of non-standard PoE devices
- ✓ IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- ✓ Total PoE power budget: 60W, up to 30W per port
- ✓ PoE Auto-check function

Aprašymas

The LevelOne FEP-0631 is a Fast Ethernet PoE switch with a total of 6 ports, two of which is available as uplink port and 4 ports for Power over Ethernet. Per PoE port a power supply of up to 30W is possible. The total PoE power budget is 60W. Distances up to 250m at 10Mbps is supported. It is an ideal solution when users use a combination of PoE and non-PoE devices. The FEP-0631 four PoE-enabled ports make it the ideal solution for users using PoE-enabled devices in the workplace. This can include a mix of PoE IP phones, PoE Wifi APs and PoE IP cams. It is the perfect solution for environments that want to upgrade their equipment and LAN infrastructure to PoE capability. The switch automatically detects the connected IEEE 802.3at/af standard device and provides these devices with power and data over a single cable. In addition, the FEP-0631 enables users to provide a stable and reliable high-speed LAN environment with store-and-forward switching architecture, packet error filtering and blockage-free packet forwarding. The 802.3x flow control mechanisms operate in both full and half duplex modes. This device supports the N-Way Auto Negotiation protocol, which automatically detects network speed and duplex mode. For instant fault detection, the FEP-0631 is equipped with a full range of LEDs to help monitor and troubleshoot the network.

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Netzwerk > Switches [+1398][-565]

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	6
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Fast Ethernet (copper) ports quantity	4

Network

Networking standards	IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Ethernet LAN data rates	10,100 Mbit/s

Optical fiber

Transmission distance (max)	0.25 km
-----------------------------	---------

Data transmission

MAC address table	1000 entries
Packet buffer memory	0.448 MB

Design

Rack mounting	No
Stackable	No
Product colour	Black
Housing material	Metal
LED indicators	Link, PoE, Power

Performance

Fanless	Yes
---------	-----

Power

Power supply included	Yes
DC input voltage	48 - 57 V
Input current	1.25 A

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	4
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	60 W

Operational conditions

Operating temperature (T-T)	-10 - 50 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Weight & dimensions	
Width	80 mm
Depth	30 mm
Height	135 mm
Weight	340 g
Packaging content	
Cables included	AC
Quick start guide	Yes
Packaging data	
Package type	Box
Package width	72 mm
Package depth	145 mm
Package height	202 mm
Package weight	350 g
Technical details	
Pallet net height	150 cm
Pallet net length	80 cm
Pallet net width	120 cm
Certificates	
Certification	CE/FCC
Logistics data	
Country of origin	China
Harmonized System (HS) code	85176990