

TP-Link Festa FS308G Managed L2/L2+ Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) White

 Gamintojas: **TP-LINK** · Modelis: **FESTA FS308G** · EAN: **8885020622379** · Prekės kodas: **651886**


97,90 €

Kaina su PVM

 Be PVM: **80,91 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8× Gigabit ports (Port 8 supports PoE input)
- ✓ Free cloud centralized management via the Festa app or the web
- ✓ Easy setup and use
- ✓ Zero-Touch Provisioning (ZTP) and Self-Organizing Network (SON)
- ✓ Complete SMB-Lite Festa Ecosystem, ideal for small businesses, home offices, cafes, retail, prosumers, advanced consumers, and large households
- ✓ Static Routing, VLAN, ACL, and IGMP Snooping
- ✓ Fanless design for silent operation
- ✓ Elegant metal casing and desktop/wall mounting design



Aprašymas

Festa – A Networking Solution Built For Small Business, No IT Required

Festa offers business-class features with consumer-inspired simplicity. Our free cloud-based centralized management is accessible via the Festa app or web, providing essential features for small businesses without the complexity required by larger-scale operations.

VLAN for Security

Helps to create network with higher security and better overall performance by dividing network into smaller groups.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Management features	
Switch type	Managed
Switch layer	L2/L2+
Cloud-managed	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Network	
Flow control support	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Spanning tree protocol	Yes
Auto-negotiation	Yes
Data transmission	
MAC address table	8000 entries
Switching capacity	16 Gbit/s
Jumbo frames support	Yes
Jumbo frames	9
Packet forwarding rate (1 Gbps)	11.9 pps
Packet buffer memory	4.1 MB
Security	
DHCP features	DHCP relay, DHCP server
IGMP snooping	Yes
Multicast features	
Multicast MAC address table	8000 entries
Design	
Product colour	White
LED indicators	Yes
Wall mountable	Yes
Performance	

Fanless	Yes
Power	
Power source	DC
Power supply included	Yes
DC input voltage	12 V
Input current	1 A
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	209 mm
Depth	126 mm
Height	26 mm
Packaging content	
Cables included	Power
Packaging data	
Package type	Box
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC)