

TP-Link Festa FS318GP L2/L2+ Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE)

Gamintojas: **TP-LINK** · Modelis: **FESTA FS318GP** · EAN: **8885020621488** · Prekės kodas: **651888**



260,90 €

Kaina su PVM

Be PVM: **215,62 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 16× Gigabit 802.3af/at PoE+ ports and 2× Gigabit SFP slots
- ✓ 150 W total PoE budget with up to 30 W PoE output per port*
- ✓ Complete business-class Festa Ecosystem with consumer-inspired simplicity
- ✓ Free cloud centralized management via the Festa app or the web†
- ✓ Easy setup and use
- ✓ Zero-Touch Provisioning (ZTP) and Self-Organizing Network (SON)
- ✓ Static Routing, VLAN, ACL, and IGMP Snooping
- ✓ Elegant metal casing and rack-mountable design



Aprašymas

Festa unifies APs, switches, and routers/gateways for full cloud-based management, offering an easy, effective, and reliable business-level network controlled via app or web. Perfect for small businesses, home offices, and cafes.

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Netzwerk > Switche [+1398][-565]

Management features

Switch layerL2/L2+

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	16
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
SFP module slots quantity	2

Network

Networking standards	IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3z
10G support	No
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Auto MDI/MDI-X	Yes
VLAN support	Yes

Data transmission

MAC address table	8000 entries
Switching capacity	36 Gbit/s
Forwarding rate	26.78 Mpps
Jumbo frames support	Yes
Packet buffer memory	4.1 MB

Security

DHCP features	DHCP relay, DHCP server, DHCP snooping
Access Control List (ACL)	Yes
IGMP snooping	Yes
IP-MAC-Port binding	Yes

Design

Rack mounting	Yes
LED indicators	Yes

Performance

Internal memory	256 MB
Flash memory	32 MB

Firmware upgradeable	Yes
Fanless	Yes
Power	
Power source	AC/PoE
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	150 W
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	440 mm
Depth	180 mm
Height	44 mm