

LevelOne FGP-1031 network switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Gamintojas: **LEVELONE** · Modelis: **FGP-1031** · EAN: **4015867228166** · Prekės kodas: **651909**



115,91 €

Kaina su PVM

Be PVM: **95,79 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8 10/100 Mbps PoE ports/ 2 Port Gigabit
- ✓ First port supports output HiPoE_60W
- ✓ IEEE 802.3af/at PoE compliant to simplify deployment and installation
- ✓ IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- ✓ 1000Mbps full-duplex, 10/100Mbps full/half-duplex, auto-negotiation, auto-MDI/MDIX

Aprašymas

The FGP-1031 switch provides 10 port 10/100 ports with 2 port 1000/100/10 Mbps uplink port. It is designed for easy installation and high performance in an environment where traffic is on the network and the number of users increases continuously. The FGP-1031 provides you with 8 PSE PoE ports, the first of which can even supply up to 60W. That can solve the limitation of the power outlet location and offer the system designer a flexible solution to locate the network device everywhere. The device size is specifically designed for medium to large workgroups. The Switch can be installed where space is limited; moreover it provides smooth network migration and easy upgrade to network capacity.

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Netzwerk > Switches [+1398][-565]

Management features

Switch type

Unmanaged

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	10
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Fast Ethernet (copper) ports quantity	8
Gigabit Ethernet (copper) ports quantity	2
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x
10G support	No
Full duplex	Yes
Half duplex	Yes
Ethernet LAN data rates	100,1000 Mbit/s
Auto-negotiation	Yes
VLAN support	Yes
Data transmission	
MAC address table	2000 entries
Design	
Rack mounting	No
Stackable	No
Product colour	Black
LED indicators	Activity, Link, PoE, Power
Performance	
Fanless	Yes
Mean time between failures (MTBF)	5000 h
Power	
Power source	AC
AC input voltage	100 - 240 V
Power consumption (typical)	5 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Total Power over Ethernet (PoE) budget	120 W
Operational conditions	
Operating temperature (T-T)	-10 - 55 °C

Storage temperature (T-T)	-40 - 75 °C
---------------------------	-------------

Operating relative humidity (H-H)	5 - 90%
-----------------------------------	---------

Storage relative humidity (H-H)	5 - 95%
---------------------------------	---------

Weight & dimensions

Width	210 mm
-------	--------

Depth	150 mm
-------	--------

Height	35 mm
--------	-------

Weight	790 g
--------	-------

Packaging content

Cables included	AC
-----------------	----

Quick start guide	Yes
-------------------	-----

Packaging data

Package width	264 mm
---------------	--------

Package depth	217 mm
---------------	--------

Package height	67 mm
----------------	-------

Package weight	1.14 kg
----------------	---------

Logistics data

Country of origin	China
-------------------	-------

Harmonized System (HS) code	85176990
-----------------------------	----------