

LevelOne RJ45 to SC Managed Fast Ethernet Media Converter, Single-Mode Fiber, 20km

Gamintojas: **LEVELONE** · Modelis: **FVS-3120** · EAN: **4015867160183** · Prekės kodas: **652065**



97,90 €

Kaina su PVM

Be PVM: **80,91 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ 100 Mbit/s 20000 m
- ✓ Ethernet LAN (RJ-45) ports: 1 DC-in jack
- ✓ Single-mode Fiber ports quantity: 1 SC 3/125,8.7/125,9/125,10/125 μm
- ✓ Grey



Aprašymas

The LevelOne Web Smart Media Converter FVS-3120 is designed to make conversion between 10/100BASE-TX and 100BASE-LX SMF SC Ethernet.

With web-based management, the network administrator can logon to the converter remotely to monitor, configure and control the status of each unit. The overall network reliability is enhanced, and the network efficiency is also improved to accommodate and deliver high bandwidth applications.

- HTTP Management with remote firmware upgrade supported
- ICMP and ARP protocols supported
- DHCP Client for easy IP address setup
- LLR (Link Loss Return) supported

- IEEE 802.1Q VLAN and Double VLAN (Q-in-Q) supported
- Support 802.3x Flow Control to prevent lost data by controlling the device flow loading

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Network	
Maximum data transfer rate	100 Mbit/s
Converter input interface	10Base-T, 100Base-TX
Converter output interface	100Base-LX
Networking standards	IEEE 802.1Q, IEEE 802.3, IEEE 802.3ah, IEEE 802.3u, IEEE 802.3x
Ethernet interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Jumbo frames support	Yes
Flow control support	Yes
Performance	
Maximum transfer distance	20000 m
Fiber mode structure	Single-mode
Fiber cable diameters supported (core/cladding)	3/125,8.7/125,9/125,10/125 μm
Features	
Internal	No
Product colour	Grey
Ports & interfaces	
Fiber optic connector	SC
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
DC-in jack	Yes
Power	
Input voltage	5 V
Input current	1 A
Power consumption (typical)	1.5 W
External power adapter	Yes
Weight & dimensions	

Width	70.3 mm
Depth	94 mm
Height	26.2 mm
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Operating relative humidity (H-H)	5 - 90%
Packaging content	
Manual	Yes
Packaging data	
Package width	160 mm
Package depth	220 mm
Package height	60 mm
Package weight	460 g
Certificates	
Certification	FCC Part 15 Class A, CE
Logistics data	
Country of origin	Taiwan