

LevelOne RJ45 to SC Fast Ethernet Media Converter, Multi-Mode Fiber, 2km, PoE PD

 Gamintojas: **LEVELONE** · Modelis: **FVT-0103TXFC** · EAN: **4015867125656** · Prekės kodas: **652067**


84,91 €

Kaina su PVM

 Be PVM: **70,17 €**


Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ 100 Mbit/s
- ✓ Ethernet LAN (RJ-45) ports: 1
- ✓ Multi-mode Fiber ports quantity: 1 SC 50/125,62.5/125,100/140 μm
- ✓ Black



Aprašymas

LevelOne's FVT-0103TXFC is new Power-over-Ethernet-converter that transfer data from 10/100BaseTX copper to fiber interfaces. These PoE Converters are designed to receive data and power from PoE networks and then to refer data out through fiber connections thus eliminating extra power cables to extend the usefulness of the network.

LevelOne's PoE converter complies with IEEE802.3af standard. The10/100 Base-TX port auto-senses 10 or 100Mbps connection speeds, auto-negotiates half-/full-duplex modes, and auto-selects MDI-X media type. FVT-0103TXFC with high-quality Multi-mode SC optical fiber connector port, this converter will give your PoE network the ability to interface with fiber connections over a distance of up to 2km.

With its compact design, our PoE converter easily fit on any limited space. No software is required. You can easily active this device by simply connecting it to the network cable and it's ready to go.

- 10/100BASE-TX UTP to 100BASE-FX fiber media conversion
- Multi-mode transmission over fiber, up to 2 km
- High-quality SC optical fiber connector port
- Complies with IEEE 802.3af PoE standard as a PD device
- Over-current protection and under-current detection
- DIP Switch for customized configurations

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Network	
Maximum data transfer rate	100 Mbit/s
Converter input interface	10Base-T, 100Base-TX
Converter output interface	100Base-FX
Networking standards	IEEE 802.3, IEEE 802.3af, IEEE 802.3u, IEEE 802.3x
Ethernet interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Packet forwarding rate (10 Mbps)	14880 pps
Packet forwarding rate (100 Mbps)	148800 pps
Duplex system	Full, Half
Cable types supported	Fiber
Performance	
Fiber mode structure	Multi-mode
Fiber cable diameters supported (core/cladding)	50/125,62.5/125,100/140 μm
Features	
Internal	No
LED indicators	FDX, Activity, Link, PoE, Power
Product colour	Black
Ports & interfaces	
Fiber optic connector	SC
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
Power over Ethernet (PoE) ports quantity	1
Power	
Output current (48V)	0.06 A

Power over Ethernet (PoE)	Yes
---------------------------	-----

Weight & dimensions

Width	94 mm
Depth	71 mm
Height	26 mm
Weight	220 g

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Operating relative humidity (H-H)	5 - 90%

Packaging data

Package width	120 mm
Package depth	55 mm
Package height	235 mm
Package weight	430 g

Certificates

Certification	FCC, CE
---------------	---------

Logistics data

Country of origin	Taiwan
Harmonized System (HS) code	85176990