LevelOne RJ45 to SC Fast Ethernet Media Converter, Single-Mode Fiber, 1550nm, 80km

Gamintojas: **LEVELONE** · Modelis: **FVT-1105** · EAN: **4015867208076** · Prekės kodas: **652068**

128,90 €

Kaina su PVM

Be PVM: **106,53 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports the transmission of extra-long packets up to 1.6KB
- ✓ IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- ✓ Single-mode fiber with SC connector for transmission of up to 80km
- ✓ Supports low-time lag transmission

Aprašymas

The FVT-1105 SMF SC media converter is able to convert network signals between copper and fiber-optic based networks. The converter provides a 10/100Base-TX RJ-45 port, supports full duplex and half duplex switch connectivity and 10Base-T and 100Base-TX auto-sensing. Used in single-mode with fiber-optic cabling, this can extend a network range up to 80km.
The converter can be used as a standalone unit or as a slide-in module to the CHV-2000 19” Converter Chassis, which can accommodate up to 14 units for use in a central wiring closet.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]

Network	
Maximum data transfer rate	100 Mbit/s
Converter input interface	10Base-T, 100Base-TX
Converter output interface	100Base-FX
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Ethernet interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Copper ethernet cabling technology	10BASE-T
Fiber ethernet cabling technology	100BASE-FX
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Store-and-forward	Yes
Duplex system	Full
Performance	
Maximum transfer distance	80000 m
Wavelength	1550 nm
Fiber mode structure	Single-mode
Fiber cable diameters supported (core/cladding)	50/125,62.5/125 µm
Mean time between failures (MTBF)	100000 h
Features	
Internal	Yes
LED indicators	Yes
Product colour	Black
Ports & interfaces	
Fiber optic connector	SC
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
DC-in jack	Yes
Power	
Input voltage	5 V
Input current	1 A
Weight & dimensions	

Width	94 mm
Depth	71 mm
Height	26 mm
Weight	200 g
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Packaging content	
AC adapter included	Yes
Quick installation guide	Yes
Packaging data	
Package width	230 mm
Package depth	150 mm
Package height	58 mm
Package weight	300 g
Package type	Box
Certificates	
Compliance certificates	RoHS
Certification	CE
Logistics data	
Country of origin	China
Harmonized System (HS) code	85176990
Master (outer) case width	440 mm
Master (outer) case length	420 mm
Master (outer) case height	305 mm
Master (outer) case gross weight	32 kg
Products per master (outer) case	40 pc(s)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903