

LevelOne 5-Port Gigabit PoE Switch, 802.3at/af PoE, 4 PoE Outputs, 60W

Gamintojas: **LEVELONE** · Modelis: **GEP-0523** · EAN: **4015867207437** · Prekės kodas: **652198**



95,90 €

Kaina su PVM

Be PVM: **79,26 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ IEEE 802.3af/at PoE compliant to simplify deployment and installation
- ✓ 10/100/1000Mbps wire speed transmission and reception
- ✓ Auto-detection and protection of non-standard PoE devices
- ✓ IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- ✓ Total PoE power budget: 60W, up to 30W per port



Aprašymas

The LevelOne GEP-0523 is a Gigabit Ethernet PoE switch with a total of 5 ports, one of which is available as uplink port and 4 ports for Power over Ethernet. Per PoE port a power supply of up to 30W is possible. The total PoE power budget is 60W. It is an ideal solution when office and home users use a combination of PoE and non-PoE devices.

The GEP-0523's four PoE-enabled ports make it the ideal solution for office users using PoE-enabled devices in the workplace. This can include a mix of PoE IP phones, PoE Wifi APs and PoE IP cams. It is the perfect solution for offices that want to upgrade their office equipment and LAN infrastructure to PoE capability or upgrade with Gigabit performance. The switch automatically detects the connected IEEE 802.3at/af standard device and provides these devices with power and data over a single cable.

In addition, the GEP-0523 enables users to provide a stable and reliable high-speed LAN environment with store-and-forward switching architecture,

packet error filtering and blockage-free packet forwarding. The 802.3x flow control mechanisms operate in both full and half duplex modes. This device supports the N-Way Auto Negotiation protocol, which automatically detects network speed and duplex mode.

For instant fault detection, the GEP-0523 is equipped with a full range of LEDs to help monitor and troubleshoot the network.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Management features	
Traffic classification	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	5
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
10G support	No
Data transmission	
MAC address table	8000 entries
Store-and-forward	Yes
Maximum data transfer rate	1000 Gbit/s
Jumbo frames support	Yes
Jumbo frames	9126
Packet buffer memory	1 MB
Design	
Rack mounting	No
Product colour	Black
Performance	
Mean time between failures (MTBF)	30000 h
Power	
Power supply included	Yes
DC input voltage	52 - 57 V
Input current	1.25 A
Power consumption (typical)	5 W

Power protection features	Over current, Short circuit
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	4
Total Power over Ethernet (PoE) budget	60 W
Operational conditions	
Operating temperature (T-T)	-20 - 70 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	96 mm
Depth	30 mm
Height	111 mm
Weight	350 g
Packaging content	
Quick start guide	Yes
Packaging data	
AC adapter included	Yes
Package width	190 mm
Package depth	55 mm
Package height	230 mm
Package weight	750 g
Certificates	
Certification	CE,FCC
Logistics data	
Harmonized System (HS) code	85176990