

LevelOne Hilbert 10" 8-Port Gigabit Smart Lite Switch, 8 x Gigabit RJ45 (10/100/1000)

Gamintojas: **LEVELONE** · Modelis: **GES-2208** · EAN: **4015867229972** · Prekės kodas: **652222**



84,91 €

Kaina su PVM

Be PVM: **70,17 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8 Gigabit Ethernet ports
- ✓ 1000Mbps full-duplex, 10/100Mbps full/half-duplex, auto-negotiation, auto-MDI/MDIX
- ✓ Supports 4K MAC address auto-learning and auto-aging
- ✓ 9K jumbo frames to increase data transfer rates
- ✓ IP Multicast Filtering through IGMP Snooping V1 / V2
- ✓ 802.1Q tag-based VLAN allows network segmentation to enhance performance and security
- ✓ IEEE 802.1p QoS with 4 priority queues
- ✓ Supports unknown unicast / broadcast / multicast storm control
- ✓ Minimize carbon footprint with advanced energy efficient technology (IEEE 802.3az)
- ✓ 4KV surge protection, 6KV contact / 8KV air ESD protection



Aprašymas

If you're in search of a networking solution that fits your 10-inch rack/enclosure, the LevelOne GES-2208 Hilbert gigabit smart lite switch is an excellent option. This next-generation Ethernet switch delivers better functionality and usability, making it cost-effective for businesses and organizations.

The switch offers 8 (10M/100M/1G) RJ45 ports and is compatible with the latest LevelOne IP Locator, the easiest-to-use switch discovery tool, which can search all Hilbert series switches and instantly know forgotten IP and other info. Additionally, it's compatible with mainstream Windows and Mac

operating systems.

With both dumb and smart Switchable usage modes, the switch is easily configurable using a DIP switch. It provides high-speed connectivity for all your devices, with 8 Gigabit ports. The support for 802.1q VLAN allows you to segment your network for enhanced security and performance.

The switch supports Port Mirroring, which allows you to monitor network traffic in real-time. Additionally, with Port-Based/802.1p/DSCP priority QoS and support for Storm Control, you can prioritize network traffic correctly and ensure that your network remains secure.

The advanced features like Loop Detection/Prevention make sure your network is always safe and reliable. Moreover, the web-based user interface and Smart-Configuration Utility make IP configuration a breeze. Upgrade your networking today with this powerful switch, and enjoy the ultimate performance, security, and ease of use.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	8
Power connector	AC-in jack
Network	
Networking standards	IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Port mirroring	Yes
Full duplex	Yes
Half duplex	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Auto MDI/MDI-X	Yes

Auto-negotiation	Yes
MAC address auto-learning supported	Yes
MAC address auto-aging supported	Yes
VLAN support	Yes
Number of VLANs	32
Data transmission	
MAC address table	4000 entries
Switching capacity	16 Gbit/s
Forwarding rate	11.904 Mpps
Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	1.5 MB
Security	
IGMP snooping	Yes
Design	
Rack mounting	Yes
Stackable	No
Product colour	Black
LED indicators	Activity, Link, Power
Performance	
Flash memory	2 MB
Noise level	0 dB
Fanless	Yes
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (typical)	6 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-40 - 70 °C

Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 95%
Heat dissipation	20.4 BTU/h
Weight & dimensions	
Width	215 mm
Depth	150 mm
Height	44.5 mm
Weight	720 g
Packaging content	
Cables included	AC
Quick start guide	Yes
Rack mount kit	Yes
Packaging data	
Package type	Box
Package width	285 mm
Package depth	257 mm
Package height	62 mm
Package weight	1.19 kg
Certificates	
Certification	CE, UKCA, FCC Part 15, Subpart B Class B, RoHS
Logistics data	
Country of origin	China