

LevelOne 5-Port Gigabit Switch, 1 x SFP

Gamintojas: **LEVELONE** · Modelis: **GEU-0521** · EAN: **4015867173480** · Prekės kodas: **652224**



83,90 €

Kaina su PVM

Be PVM: **69,34 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4 Gigabit Ethernet ports and 1 Gigabit SFP slot
- ✓ 9K jumbo frames to increase data transfer rates
- ✓ 1000Mbps full-duplex, 10/100Mbps full/half-duplex, auto-negotiation, auto-MDI/MDIX
- ✓ Supports 1K MAC address auto-learning and auto-aging
- ✓ IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- ✓ Provides wall or desktop mounting
- ✓ Quick and easy installation



Aprašymas

GEU-0521 is designed to make conversion between 10/100/1000Base-T and 1000Base-SX/LX Fiber Ethernet. The overall network flexibility is enhanced, and the network efficiency is also improved to accommodate and deliver high bandwidth applications.

Providing 10Gbps internal switching fabric, the GEU-0521 can handle an extremely large amount of data in a secure topology linking to a backbone or high capacity servers. The GEU-0521 provides 4K MAC address table, 9K bytes JUMBO Frame, and offers wire-speed packet transfer performance without risk of packet loss. The high data throughput of the device makes it ideal for most Gigabit environments, especially for the network to be upgraded to a Gigabit environment.

Techninė specifikacija

Specifications

Sandėlio grupė Server, Storage & Netzwerk > Switche [+1398][-565]

Management features

Switch type Unmanaged

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity 4

Basic switching RJ-45 Ethernet ports type Gigabit Ethernet (10/100/1000)

Installed SFP modules quantity 0

Installed SFP+ modules quantity 0

SFP module slots quantity 1

Fiber optic connector SFP

Network

Networking standards IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z

10G support No

Copper ethernet cabling technology 10BASE-T, 100BASE-TX, 1000BASE-T

Cable types supported Cat5, Cat5e

Full duplex Yes

Flow control support Yes

Auto MDI/MDI-X Yes

Auto-negotiation Yes

MAC address auto-learning supported Yes

MAC address auto-aging supported Yes

Optical fiber

Fiber ethernet cabling technology 1000BASE-LX, 1000BASE-SX

Transmission distance (max) 0.55 km

Data transmission

MAC address table 4000 entries

Switching capacity 1 Gbit/s

Store-and-forward Yes

Jumbo frames support Yes

Jumbo frames 9000

Packet forwarding rate (1 Gbps) 1488000 pps

Packet forwarding rate (100 Mbps) 148800 pps

Packet forwarding rate (10 Mbps) 14880 pps

Packet buffer memory	1 MB
----------------------	------

Design

Rack mounting	No
Product colour	Grey
Housing material	Metal
LED indicators	Activity, Link, Power
Wall mountable	Yes

Power

AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Input current	2.5 A

Power over Ethernet (PoE)

Power over Ethernet (PoE)	No
---------------------------	----

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 90 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	96 mm
Depth	112 mm
Height	30 mm
Weight	380 g

Packaging content

Quick start guide	Yes
-------------------	-----

Packaging data

AC adapter included	Yes
Rubber feet	Yes
Package width	140 mm
Package depth	250 mm
Package height	55 mm
Package weight	540 g

Certificates

Certification	FCC Class B, CE
---------------	-----------------

Logistics data

Country of origin	China
Harmonized System (HS) code	85176990