

LevelOne 5-Port Unmanaged 2.5-Gigabit Ethernet Switch

Gamintojas: **LEVELONE** · Modelis: **GEU-0525** · EAN: **4015867237793** · Prekės kodas: **652227**



70,91 €

Kaina su PVM

Be PVM: **58,60 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 5 x 100/1000/2500 Base-T RJ45 copper ports
- ✓ 2500Mbps full-duplex, 100/1000Mbps full/half-duplex, auto-negotiation, auto-MDI/MDIX
- ✓ Supports 8K MAC address auto-learning and auto-aging
- ✓ 15K jumbo frames to increase data transfer rates
- ✓ IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- ✓ Desktop and Wall mount design
- ✓ Quick and easy installation



Aprašymas

2.5-Gigabit Speeds: Take Your Data to the Next Level

The GEU-0525 is a 5-port 2.5-Gigabit Ethernet Switch that gives you a high-performance, low-cost, easy-to-use, seamless upgrade to boost your network to 2500Mbps.

Bandwidth hungry? Not a problem.

What happens when you have several users accessing multimedia applications all at the same time? No need to worry as GEU-0525 allows you to move large files faster and easier. Transfer your CGI, CAD, video, or other large multimedia files over the network instantly and without lag.

Plug and Play, Flexible and Easy

The GEU-0525 is plug-and-play so no configuration is required. Providing auto MDI/MDI-X cable detection on all ports eliminates the need for

crossover cables or Uplink ports. Each port can be used as general ports or Uplink ports, and any port can be simply plugged into a server, a hub, a router or a switch, using a straight cable or crossover cable. Diagnostic LEDs which display link status and activity, allowing you to quickly detect and correct problems on the network.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Management features	
Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	5
Basic switching RJ-45 Ethernet ports type	2.5G Ethernet (100/1000/2500)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
2.5G Ethernet (copper) ports quantity	5
Network	
Networking standards	IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T, 2500BASE-T
Full duplex	Yes
Half duplex	Yes
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
MAC address auto-learning supported	Yes
MAC address auto-aging supported	Yes
Data transmission	
MAC address table	8000 entries
Switching capacity	25 Gbit/s
Forwarding rate	18.6 Mpps
Jumbo frames support	Yes
Jumbo frames	15000
Packet buffer memory	4 MB
Design	
Product colour	Black

LED indicators	Activity, Link, Power
Wall mountable	Yes
Performance	
Noise level	0 dB
Fanless	Yes
Power	
Power source	DC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	0.4 A
Input voltage	12 V
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	175.5 mm
Depth	105.3 mm
Height	27.3 mm
Weight	476.7 g
Packaging content	
Quick start guide	Yes
Packaging data	
AC adapter included	Yes
Package width	190 mm
Package depth	115 mm
Package height	82 mm
Package weight	614.4 g
Technical details	
Master (outer) cases per pallet (air)	12 pc(s)

Pallet gross length	80 cm
Pallet gross width	120 cm
Pallet height (air)	148.2 cm
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), RoHS, UKCA
Logistics data	
Country of origin	China
Master (outer) case width	605 mm
Master (outer) case length	400 mm
Master (outer) case height	440 mm
Harmonized System (HS) code	851762
Master (outer) case gross weight	33 kg
Products per master (outer) case	50 pc(s)