

LevelOne 16-Port Gigabit Switch

Gamintojas: **LEVELONE** · Modelis: **GEU-1621** · EAN: **4015867164914** · Prekės kodas: **652230**



103,90 €

Kaina su PVM

Be PVM: **85,87 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Minimize carbon footprint with advanced energy efficient technology (IEEE 802.3az)
- ✓ 10/100/1000Mbps wire speed transmission and reception
- ✓ Supports 8K MAC address auto-learning and auto-aging
- ✓ 9K jumbo frames to increase data transfer rates
- ✓ 16 Gigabit Ethernet ports
- ✓ 19-inch rackmount kit included



Aprašymas

The GEU-1621 is equipped with 16 Gigabit ports that lead you to a real Gigabit connections. Users are able to transfer large and high bandwidth-needed files faster, and hence get a real improvement of efficiency. Offers a fast and reliable network. The store-and-forward architecture filters errors and forwards packets in a non-blocking environment. Flow control ensures the correctness of data transmitting. The IEEE 802.3x and backpressure flow control mechanisms work respectively for full and half duplex modes. Power Saving Features The GEU-1621 supports IEEE 802.3az Energy Efficient Ethernet to provide power-saving benefits without compromising the performance. The switch automatically enters the sleep mode, if there is no link activity detected, using less energy than idling at full power. Easy Installation and Maintenance The switch supports Nway auto-negotiation protocol to detect the networking speed (10/100/1000 Mbps) and the duplex modes (Full/Half) automatically. Auto-MDI/MDI-X function eliminates the effort to use crossover cables. Diagnostic LEDs are provided to get real-time information of the connection status and network.

Techninė specifikacija

Specifications

Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
----------------	--

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	16
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	16

Network

Networking standards	IEEE 802.3ab, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x
10G support	No
Full duplex	Yes
Half duplex	Yes
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
MAC address auto-learning supported	Yes
MAC address auto-aging supported	Yes

Data transmission

MAC address table	8000 entries
Switching capacity	32 Gbit/s
Forwarding rate	1.488 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	9000

Design

Rack mounting	Yes
Product colour	Grey

Performance

Built-in processor	Yes
Processor model	Realtek RTL8382L
Flash memory	4 MB

Power

AC input voltage	100 - 240 V
------------------	-------------

AC input frequency	50 - 60 Hz
Power consumption (typical)	10.1 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	280 mm
Depth	180 mm
Height	44 mm
Weight	2.6 kg
Packaging content	
Manual	Yes
Rack mount kit	Yes
Packaging data	
Package type	Box
Package width	258 mm
Package depth	340 mm
Package height	66 mm
Package weight	1.7 kg
Technical details	
Pallet gross length	80 cm
Pallet gross width	120 cm
Pallet height (air)	155.5 cm
Logistics data	
Products per pallet	22 pc(s)
Country of origin	China
Master (outer) case width	353 mm
Master (outer) case length	355 mm
Master (outer) case height	280 mm
Harmonized System (HS) code	85176990

Master (outer) case gross weight	10.4 kg
Products per master (outer) case	5 pc(s)